

25X1

**Page Denied**

## PROCESSING COPY

OK

## INFORMATION REPORT INFORMATION REPORT

## CENTRAL INTELLIGENCE AGENCY

This material contains information affecting the National Defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C. Secs. 793 and 794, the transmission or revelation of which in any manner to an unauthorized person is prohibited by law.

C-O-N-F-I-D-E-N-T-I-A-L

25X1

## COUNTRY

China

## REPORT

## SUBJECT

Catalogs of Chinese Communist Exports

## DATE DISTR.

18 February 1957

## NO. PAGES

2

## REQUIREMENT NO.

RD

## REFERENCES

25X1

## DATE OF INFO.

## PLACE &amp; DATE ACQ.

catalogs of exports from Communist China

- a. "Mouse" Tubular paper condenser, exported by the China National Instruments Import Corporation (CNIIC). (In English; folder)
- b. Bestone Radio Coil Mfg. Catalog, exported by CNIIC, Shanghai. (as above)
- c. China Resources Co. Export Catalog (Machinery, Scientific Instrument, Chemical, and Pharmaceutical Divisions. This is a loose-leaf catalog containing, in addition to a series of pictures and descriptions of machines of various types, lists of items exported by the following corporations:
  - (1) China National Import and Export Corporation - Chinese proprietary medicines, industrial and fine chemicals.
  - (2) China National Foodstuffs Export Corporation - Chinese proprietary medicines.
  - (3) China National Native Produce Export Corporation - fine chemicals and Chinese proprietary medicines.
  - (4) China National Machinery Import Corporation - general machinery, machine tools, mining machinery, power equipment, electrical machinery, ball and roller bearings.
  - (5) China National Transport Machinery Import Corporation - textile machinery, knitting machines, industrial sewing machines, wood-working machinery, printing press machinery, foodstuff industry machinery, and others.
  - (6) China National Instruments Import Corporation - electrical instruments, telephone sets, radios and accessories, cinematographic and photographic equipment, engineering instruments, laboratory instruments and apparatus, and others.

Attachments are unclassified when detached from this report.

25X1

C-O-N-F-I-D-E-N-T-I-A-L

25X1

STATE	X	ARMY	X	NAVY	X	AIR	X	FBI	X	AEC	X	BFC	X	Treas	X
-------	---	------	---	------	---	-----	---	-----	---	-----	---	-----	---	-------	---

(Note: Washington distribution indicated by "X"; Field distribution by "#".)

25X1


**Page Denied**

25X1

# BESTONE RADIO COIL MFG.

SHANGHAI, CHINA.

## CATALOGUE



Exported by:

China National Instruments Import Corporation.

Shanghai, China.



## Model 500 Paper Form Superheterodyne Circuit Receiver Coil

CODE	DESCRIPTIONS
551	Medium wave broadcasting band coil, for 6SA7 converter. Every set containing one antenna coil and one oscillator coil. Frequency range: 550-1650 kc. Paper form: dia. 12.5 m/m. len. 31 m/m. Antenna coil secondary universal wound by litz wire. Coils sealed with wax. .....
552	Medium wave broadcasting band coil, for 6A8, 6K8, 1A7GT, 1LA6 and 1R5 converters. Frequency range and other specifications same as 551. .....
553	Made for Medium and short wave bands of 6SA7 converter. Every set containing one antenna coil and one oscillator coil. Frequency range: 550-1650 kc. 6-18 mc. Paper form dia. 16 m/m. len. 48.5 m/m. Medium wave antenna coil secondary universal wound by litz wire. Coils sealed with wax. .....
554	Two bands coil, made for 6A8, 6K8, 1A7GT, 1LA6, 1LC6 and 1R5 converters. Frequency range and other specifications same as 553. .....
555	Three bands coil, for 6SA7 converters. Every set containing one antenna coil and one oscillator coil. Frequency covered in the three bands: 550-1650 kc. 2.2-7.5 mc. 7-22 mc. Paper form dia. 16 m/m. len. 56 m/m. Coils sealed with wax. .....
556	Three bands coil, for 6A8, 6K8, 1A7GT, 1LA6, 1LC6 and 1R5 converters. Frequency range and other specifications same as 555. .....
557	Two bands high frequency coil, made for 6K7, 6SK7 and 1T4, high frequency amplifiers, should be used with 553, 554. Frequency range and other specifications same as the antenna coil of 553 & 554. .....
558	Three bands high frequency coil, made for 6K7, 6SK7 and 1T4 high frequency amplifiers, should be used with 555, 556. Frequency range and other specifications same as the antenna coil of 555 & 556.

## Model 600 Bakelite form Superheterodyne Circuit Receiver Coil

CODE	DESCRIPTIONS
610	Medium wave broadcasting band coil, Every set containing one antenna coil and one oscillator coil. Frequency range 550-1650 kc. For fitting in the characteristics of all type of converters, the coil may divide into four forms: 610-S for 6SA7 610-A for 6A8, 1A7GT 610-K for 6K8 610-R for 1R5 Coil form dia. 16 m/m. len. 25 m/m. Antenna coil secondary universal wound by litz wire. Connecting terminals besides the number, have colored sign for distinguishing. .....
620	Short wave band coil, every set containing one antenna coil and one oscillator coil. Frequency range 2.2-7.5 mc. The coil also divided into four forms: 620-S, 620-A, 620-K, 620-R. Antenna coil secondary closely wound with No. 30 enameled wire, others same as 610. .....
630	Short wave band coil, every set containing one antenna coil and one oscillator coil. Frequency range 7-22 mc. The coil also divided into four forms: 630-S, 630-A, 630-K, 630-R. Antenna coil secondary closely wound with No. 24 silver plated wire, other specifications same as 610. .....
640	Short wave band coil, every set containing one antenna coil and one oscillator coil. Frequency range 6-18 mc. The coil also divided into four forms: 640-S, 640-A, 640-K, 640-R. Method of winding and other specifications same as 630. .....
610-RF	Medium wave broadcasting band RF coil, made for 6K7, 6SK7 and 1T4 high frequency amplifiers, should be used with any form of 610. Frequency range and other specifications same as 610. .....
620-RF	Short wave band RF coil, made for 6K7, 6SK7 and 1T4 high frequency amplifiers, should be used with any form of 620. Frequency range and other specifications same as 620. .....
630-RF	Short wave band RF coil, made for 6K7, 6SK7 and 1T4 high frequency amplifiers, should be used with any form of 630. Frequency range and other specifications same as 630. .....
640-RF	Short wave band RF coil, made for 6K7, 6SK7 and 1T4 high frequency amplifiers, should be used with any form of 640. Frequency range and other specifications same as 640.

**I. F. Transformers.**

<u>CODE</u>	<u>DESCRIPTIONS</u>
1490	465 kc. plastic core I. F. Transformer, adjusting range 455-465 kc. Universal wound with litz wire. Connecting terminals fixed on a plastic base, easy for connecting. .....
1470	465 kc. iron core I. F. Transformer, adjusting range 455-465 kc. Litz wire universal wound coils on plastic tubing. Connecting terminals fixed on a plastic base.


**R. F. CHOKE**

<u>CODE</u>	<u>DESCRIPTIONS</u>
250	R. F. Choke 2.5 mh. 50 ma. Coils honey-comb wound on porcelain core. Len. 35 m/m .....
251	R. F. Choke 2.5 mh. 100 ma. (Similar in construction to the R. F. C. above.) Same as 250. .....
256	R. F. Choke Coils honey-comb wound on a stand off porcelain insulator. Inductance values of 1, 2.5 and 5 millihenries are available with a current rating of 600 milliamperes.

**Model 300 Simple Receiver Coil**

<u>CODE</u>	<u>DESCRIPTIONS</u>
336	Medium wave broadcast band 3 circuits regenerative coil, made for all types of triode and pentode tubes, universal wound on paper form of 16 m/m in diameter and 42 m/m in length. All coils are sealed with wax. .....
338	Crystal receiving set coils. Set of two used with ganged condenser, best for its selectivity and sensibility. It can be used either double circuits or single circuit as desire. Universal wound by litz wire on paper form, 16 m/m in dia. and 42 m/m in len. All coils sealed with wax.

# "mouse"



中國儀器進口公司

**"MOUSE" TUBULAR PAPER CONDENSER**

"MOUSE" Paper capacitors are sealed tight against moisture by a distinctive wax-molding process. This treatment assures longer life expectancy than ever before attained for wax sealed tubular paper capacitors.

The foil and paper employed in these capacitors are pre-tested for uniformly high quality, and winding are thoroughly impregnated. The hot-soldered tinned-copper leads provide a firm support for mounting.

Voltage ratings are consistent with the quality workmanship incorporated in this unique design. An especially important characteristic is their ability to give outstanding performance under high humidity service conditions.

Impregnation: Wax impregnated.

Terminals: Solid, tinned copper wire.

Lead sizes No. 22 SWG

No. 21 SWG

No. 20 SWG

Case Seal: External overall wax dip.

Markings: Type designation, capacitance, and voltage rating printed on tube.

Capacitance Tolerance:  $\pm 10\%$ . Special tolerances available upon request.

Insulation Resistance: 2000 megohms minimum.

Conservative D.C. Rating: Tested at 1200 volts D.C.

Catalog No.	Capacity Mfd.	Diameter	Length
ST-6T1	.0001	11 m/m	36 m/m
ST-6T2	.0002	" "	" "
ST-6T25	.00025	" "	" "
ST-6T5	.0005	" "	" "
ST-6D1	.001	" "	" "
ST-6D2	.002	" "	" "
ST-6D25	.0025	" "	" "
ST-6D3	.003	" "	" "
ST-6D4	.004	" "	" "
ST-6D5	.005	14 "	39 "
ST-6D6	.006	" "	" "
ST-6D8	.008	" "	" "
ST-6 S1	.01	" "	" "
ST-6 S15	.015	" "	" "
ST-6 S2	.02	" "	" "
ST-6 S3	.03	" "	" "
ST-6 S4	.04	15 "	39 "
ST-6 S5	.05	" "	" "
ST-6 S6	.06	" "	" "
ST-6 P1	.1	19 "	43 "

**CHINA NATIONAL INSTRUMENTS IMPORT CORPORATION**

**HEAD OFFICE:**

Er-Li-Kou, Hsi Chiao, Peking, China.

Cable Address: "INSTRIMPORT"

**BRANCH OFFICES:**

SHANGHAI: 27 Chungshan Road (E.I.).

Cable Address: "INSTRIMP"

TIENTSIN: 171 Kien Shieh Road.

Cable Address: "INSTRIMP"

CANTON: 25 Tai Ping Road, S.

Cable Address: "INSTRIMP"

華潤公司

# 出口商品目錄

(機械·儀器·化工·藥品)

CHINA RESOURCES CO.  
EXPORT CATALOGUE

MACHINERY, SCIENTIFIC INSTRUMENT,  
CHEMICAL AND PHARMACEUTICAL DIVISIONS.

地址：香港德輔道中 中國銀行大廈

ADDRESS: BANK OF CHINA BUILDING 2A DES VOEUX ROAD CENTRAL

CABLE ADDRESS: "CRECO" HONGKONG

**華潤公司代理之中國各國營專業公司名址**  
**FULL NAMES AND ADDRESSES OF CHINA NATIONAL CORPORATIONS**  
**FOR WHOM CHINA RESOURCES COMPANY ACT AS TRADE AGENTS**  
**IN HONG KONG**

**中國技術進口公司**  
 北京 東長安街，對外貿易大廈

**China National Technical Import Corporation,**  
 Foreign Trade Building,  
 Tung Chang An Street, Peking, China.  
 Cable Address: 'Techimport' Peking.

**中國進出口公司**  
 北京 台基廠頭條六號

**China National Import and Export Corporation,**  
 6, Tou Tiao Hutung, Tai Chi Chang,  
 Tung Chiao Min Hsiang, Peking, China.  
 Cable Address: 'CNIEC' Peking.

**中國五金進口公司**  
 北京 東長安街，對外貿易大廈

**China National Metals Import Corporation,**  
 Foreign Trade Building,  
 Tung Chang An Street, Peking, China.  
 Cable Address: 'Chimetals' Peking.

**中國機械進口公司**  
 北京 西直門外二里溝

**China National Machinery Import Corporation,**  
 Erh Li Kou, Outside Hsi Chih Men,  
 Peking, China.  
 Cable Address: 'Machimport' Peking.

**中國運輸機械進口公司**  
 北京 西直門外二里溝

**China National Transport Machinery Import Corporation,**  
 Erh Li Kou, Outside Hsi Chih Men,  
 Peking, China.  
 Cable Address: 'Transmach' Peking.

**中國儀器進口公司**  
 北京 西直門外二里溝

**China National Instruments Import Corporation,**  
 Erh Li Kou, Outside Hsi Chih Men,  
 Peking, China.  
 Cable Address: 'Instrimport' Peking.

**中國雜品出口公司**  
 北京 東四牌樓九條胡同(甲)三十二號

**China National Sundries Export Corporation,**  
 32A, Chiu Tiao Hutung, East City,  
 Peking, China.  
 Cable Address: 'Sundry' Peking.

**中國絲綢公司**  
 北京 南池子二十九號

**China National Silk Corporation,**  
 29, Nan Chih Tze, Peking, China.  
 Cable Address: 'Chisicorp' Peking.

**中國茶葉出口公司**  
 北京 禮士胡同五十七號

**China National Tea Export Corporation,**  
 57, Li Shih Hutung, Tung Szu Pai-lou,  
 Peking, China.  
 Cable Address: 'Nationtea' Peking.

中國礦產公司  
北京 寶興寺街三號

中國畜產出口公司  
北京 汪家胡同四號

中國糧穀油脂出口公司  
北京 豬市大街五十七號

中國食品出口公司  
北京 廣安門大街教子胡同三十八號

中國土產出口公司  
北京 虎坊橋大街四十六號

China National Minerals Corporation,  
3, Pao Chan Sze Street, Peking, China.  
Cable Address: 'Chimincorp' Peking.

China National Animal By-Products Export Corporation,  
4, Wangchia Hutung, East City, Peking, China.  
Cable Address: 'Byproducts' Peking.

China National Cereals, Oils and Fats Export Corporation,  
57, Chu Shih Ta Chieh Peking, China.  
Cable Address: 'Nationoil' Peking.

China National Foodstuffs Export Corporation,  
38, Chiao Tze Hutung, Kuang An Men Street, Peking, China.  
Cable Address: 'Foodstuffs' Peking.

China National Native Produce Export Corporation,  
46, Hu Fang Chiao Street, Peking, China.  
Cable Address: 'Prochina' Peking.

中國進出口公司經營  
EXPORTER: CHINA NATIONAL IMPORT & EXPORT CORPORATION

中國成藥  
CHINESE PROPRIETARY MEDICINES

艾羅補腦汁 大瓶	Phostose (Brain Tonic) Each bottle contains 168 cc (big bottles). 12 doz. per wooden case.
艾羅補腦汁 小瓶	Phostose (Brain Tonic) Each bottle contains 84 cc (small bottles). 24 doz. per wooden case.
五洲人造自來血 大瓶	Blood Tonic "CHI LAI" Each bottle contains 400 gms. (big bottles). 5 doz. per wooden case.
五洲人造自來血 小瓶	Blood Tonic "CHI LAI" Each bottle contains 240 gms. (small bottles). 10 doz. per wooden case.
集成痲子粉 小童用 鐵罐裝	Prickly Heat Powder "CHIH-CHEN" For children. Each tin contains 100 gms. 200 tins per wooden case.
集成痲子粉 小童用 紙罐裝	Prickly Heat Powder "CHIH-CHEN" For children. Each paper tin contains 100 gms. 200 tins per wooden case.
集成痲子粉 成年人用 鐵罐裝	Prickly Heat Powder "CHIH-CHEN" For adults. Each tin contains 100 gms. 200 tins per wooden case.
集成痲子粉 成年人用 紙罐裝	Prickly Heat Powder "CHIH-CHEN" For adults. Each paper tin contains 100 gms. 200 tins per wooden case.
艾羅咳嗽藥 大瓶	Thirocobin "YALES" (Cough Syrup) Each bottle contains 225 cc (big bottles). 10 doz. per wooden case.
艾羅咳嗽藥 小瓶	Thirocobin "YALES" (Cough Syrup) Each bottle contains 120 cc (small bottles). 20 doz. per wooden case.
阿墨林藥水(癬藥水) 大瓶	Lotion "AMOLIN" (for skin disease) Each bottle contains 54 cc (large bottles). 50 doz. per wooden case.
阿墨林藥水(癬藥水) 小瓶	Lotion "AMOLIN" (for skin disease) Each bottle contains 13 cc (small bottles). 100 doz. per wooden case.

沃古林眼水	Occulin Eye Drops, 15 c.c. "Kofa" 100 dozen per wooden case.
複方杏仁露 大瓶	Almond Cough Syrup Compound, 150cc (Large bottles).
複方杏仁露 小瓶	Almond Cough Syrup Compound, 65cc (Small bottles).
維丁膠性鈣	Colloidal Calcium with Vitamin D, 20 c.c. bottles Each c.c. contain 0.5 mg Colloidal Calcium & 5000-U Vitamin D.
五洲十滴水	Anti Cholera Drops. "GLOBE BRAND." Each bottle contains 5 cc., 1000 bottles per box, 4 boxes per wooden case.
信寧噴水 大瓶	Cough Syrup "SINECO" Each bottle contains 360 cc (Large bottles). 60 bottles per wooden case.
信寧噴水 小瓶	Cough Syrup "SINECO" Each bottle contains 180 cc (small bottles). 120 bottles per wooden case.
食母生片(乾醃母片)	Zymasun Tablet (Dried Yeast) Each bottle contains 300 tab. of 0.20 gm., 120 bottles per wooden case.
力勃隆丸	Liberon Capsules (Liver Extract & B-Complex) Each bottle contains 60 capsules. 240 bottles per wooden case.
九一四藥膏 小盒	914 Ointment Each box contains 10 gms. (small box). 100 dozen boxes per wooden case.
維血平丸 小瓶	Visculbine Tablet (for high blood pressure) Each tube contains 50 tab., 100 doz. tubes per wooden case.
維血平丸 大瓶	Visculbine Tablet (for high blood pressure) Each bottle contains 500 tab., 5 doz. bottles per wooden case.
維血平液	Visculbine Liquid (for high blood pressure) Each bottle contains 100 cc., 20 doz. bottles per wooden case.
好力生濃丸	Halisun Capsules, Strong Each capsule contains Vit. A: 10,000 I.U., Vit. D: 1,000 I.U. Each bottle contains 100 capsules. 240 bottles per wooden case.

龍虎人丹 小包	Zung Tan In packet of 60's. 5000 packets per cardboard box.
龍虎人丹 大包	Zung Tan In packet of 200's. 1000 packets per cardboard box.
龍虎人丹 瓶庄	Zung Tan In bottle of 400's. 600 bottles per cardboard box.
麻黃素片 二十粒庄	Ephedrin HCl. Tablet Each bottle contains 20 tablets of 0.025 gm. 2000 bottles per wooden case.
麻黃素片 一百粒庄	Ephedrin HCl. Tablet Each bottle contains 100 tablets of 0.025 gm. 200 bottles per wooden case.
麻黃素片 一千粒庄	Ephedrin HCl. Tablet Each bottle contains 1000 tablets of 0.025 gm. 50 bottles per wooden case.
鐘鷹牌藥子擦 大瓶	"A.C.D." Fruit Saline Each bottle contains 150 grms (big bottles).
鐘鷹牌藥子擦 小瓶	"A.C.D." Fruit Saline Each bottle contains 30 grms (small bottles).
優散痛止痛片	Eusedon Tablets (Pain Killer) Each tube contains 10 tablets.
一輕鬆通便丸 十粒庄	Tablets Isatin (Laxative) Each tube contains 10 tablets; 1000 tubes per wooden case.
一輕鬆通便丸 六十粒庄	Tablets Isatin (Laxative) Each bottle contains 60 tablets.
羊腸線	Surgical Sutures, plain and chromic.
注射器	Glass Syringes, all sizes.
針頭	Hypodermic Needles, all sizes.
血壓表	Sphygmomenometer (Blood Pressure Meter).
三用聽診器	Stethoscopes, triple change.
嬰孩秤	Baby Scales.
磅人秤	Body Scales.
脫脂紗布	Absorbent Gauze, Hospital Quality 34" x 9 yds, 1-lb p/kt.
脫脂棉棉	Absorbent Cotton, Hospital Quality, 1-lb p/kt.

香港代理處：華潤公司  
Hongkong Agency: CHINA RESOURCES CO.



中國食品出口公司經售  
EXPORTER: CHINA NATIONAL FOODSTUFFS EXPORT CORPORATION

中國成藥  
CHINESE PROPRIETARY MEDICINES

清魚肝油 瓶庄	Cod Liver Oil Pure B. P. Each bottle contains 500 gm; each gram contains Vitamin A 850-U, D 85-U 20 bottles per wooden case
高單位魚肝油精滴劑 大瓶	Cod Liver Oil Conc. High Potency with Dropper Each bottle contains 50 c.c.; each c.c. contains Vitamin A 50,000-U, D 5,000-U, 200 bots. per wooden case
高單位魚肝油精滴劑 小瓶	Cod Liver Oil Conc. High Potency with Dropper Each bottle contains 10 c.c.; each c.c. contains Vitamin A 50,000-U, D 5,000-U, 400 bots. per wooden case
魚肝油精滴劑	Cod Liver Oil Conc. with Dropper Each bottle contains 50 c.c.; each c.c. contains Vitamin A 5,000-U, D 500-U, 200 bots. per wooden case
乳白魚肝油 大瓶	Cod Liver Oil Emulsion Each bottle contains 500 gm; 50 bots. per wooden case
乳白魚肝油 小瓶	Cod Liver Oil Emulsion Each bottle contains 250 gm; 50 bots. per wooden case
麥精魚肝油	Cod Liver Oil with Malt Extract Each bottle contains 500 gm; 50 bots. per wooden case
高單位魚肝油精丸	Cod Liver Oil Conc. High Potency, Capsules Each bottle contains 100 Capsules; each Capsule contains Vitamin A 10,000-U D 1,000-U, 200 bots. per wooden case
魚肝油精丸 瓶庄	Cod Liver Oil Conc. Capsules Each bottle contains 100 Capsules; each Capsule contains Vitamin A 3,000-U D 1,000-U, 200 bots. per wooden case
魚肝油精丸 罐庄	Cod Liver Oil Conc. Capsules Each tin contains 10,000 Capsules; each Capsule contains Vitamin A 3,000-U D 1,000-U, 10 tins per wooden case

香港代理處：華潤公司  
Hongkong Agency: CHINA RESOURCES CO.

中國土產出口公司經售  
EXPORTER: CHINA NATIONAL NATIVE PRODUCE EXPORT CORPORATION

西藥原料及中國成藥  
FINE CHEMICALS & CHINESE PROPRIETARY MEDICINES

葡萄糖鈉  
中國藥典標準

Sodium Stibogluconate, Chinese Pharmacopoeia,  
1. 10-kg. tins, 4 tins to a wooden case.  
2.  $\frac{1}{2}$ -kg. bottles, 20 bottles to a wooden case.

葡萄糖鈉針

Sodium Stibogluconate Ampoules  
100 mg pentavalent Antimony per cc. Each ampoule  
contains 6 cc., 6 ampoules in one box, 250 boxes per  
case.

硫脲氮

T.B.1/698 (P-Acetylaminobenzaldehyde  
Thiosemicarbazone),  
1. 10-kg. tins, 4 tins to a wooden case.  
2.  $\frac{1}{2}$ -kg. bottles, 20 bottles to a wooden case.

香港代理處：華潤公司  
Hongkong Agency: CHINA RESOURCES CO.

中國進出口公司經售  
EXPORTER: CHINA NATIONAL IMPORT & EXPORT CORPORATION  
化工與西藥原料  
INDUSTRIAL & FINE CHEMICALS

活性炭	Activated Carbon, Decolourizing—0.1 gm dry sample can decolourize 10-8 cc of 0.15% Methylene Blue solution in 5 minutes. Packed in 20-kg. iron drums.
酒精及變性酒精	Alcohol & Denatured Alcohol.
氯化銨 純度：99%以上	Ammonium Chloride, $\text{NH}_4\text{Cl}$ , Purity—99% up. Packed in 25-kg. cloth bags, lined with 2-ply kraftpaper bags.
安尼林油 純度：99%以上	Aniline Oil, $\text{C}_6\text{H}_5\text{NH}_2$ , Aniline content (dry base) 99% up. Packed in 200-kg. iron drums.
氯化鉀 純度：98%以上	Barium Chloride, $\text{BaCl}_2 \cdot 2\text{H}_2\text{O}$ , Purity—98% up. Packed in 50-kg. wooden cases.
純 苯 比重：0.882 至 0.886	Benzene, $\text{C}_6\text{H}_6$ , Specific Gravity—0.882 to 0.886, Distillation Range—79 to 80.6°C. Packed in 160-kg. iron drums.
碳化鈣 (俗名電石)	Calcium Carbide, $\text{CaC}_2$ , Acetylene producing power per 1-kg., not less than 280 litres. Packed in 100 or 200-kg. iron drums.
輕質碳酸鈣 純度：98%以上	Calcium Carbonate, Light, $\text{CaCO}_3$ , Purity—98% up. Packed in 50-kg. cloth bags.
膠質碳酸鈣 純度：98%以上	Calcium Carbonate, Colloidal, $\text{CaCO}_3$ , Purity—98% up. Packed in 50-kg. cloth bags.
氯化鈣 純度：70%	Calcium Chloride, $\text{CaCl}_2$ , Purity—70% up. Packed in 100-kg. iron drums.
燒鹼 (即苛性鹼) 純度：96%以上 及98%以上，固體狀	Caustic Soda, $\text{NaOH}$ , $\text{NaOH}$ content not less than 96% (or 98%) (Solid & Fused). Packed in 100, 200 or 230-kg. iron drums.
二硝基氯化苯 純度：98%以上	Dinitrochlorobenzene, $\text{C}_6\text{H}_4(\text{NO}_2)_2\text{Cl}$ , Purity (Dry Base) not less than 98% up. Solidifying point (Dry base) not lower than 47.3°C. Packed in 300-kg. iron drums.
甘油松香	Ester Gum 138.
硫化油膠	Factice, (Vegetable Oil Vulcanization). Packed in 200-kg. iron drums.
糠 醛 純度：98%以上	Furfural, $\text{C}_5\text{H}_4\text{OCHO}$ , Purity—98% up. Specific Gravity—1.159 @ 20/4°C. Packed in 220-kg iron Drums

乾酪素

Lactic Casein.

立德粉

Lithopone, Purity—28-30% ZnS.

含硫化銻 28-30%

Packed in 50 kg. 4-ply paper bags, outside with gunny bags.

一氯化苯

Monochlorobenzene,  $C_6H_5Cl$ . Benzene content (dry base) not more than 0.3%, Sp. Gr.  $D_{15}^{20}$  1.112-1.114.比重: 1.112-1.114 ( $D_{15}^{20}$ )

Packed in 200-kg. iron drums.

精 萘

Naphthalene, Refined,  $C_{10}H_8$ . Purity—99% up. Melting point—79°C.

純度: 99%以上

Packed in 25/50-kg. 5-ply paper bags.

萘 丸 (即臭丸)

Naphthalene Ball, Diameter—5/8" and 3/4".

直徑: 5/8 及 3/4 吋

Packed in 50-kg. wooden cases.

各種油漆:

Paints, Various types of Quick-drying enamels, Ready mixed paints &amp; Paste paints.

快乾磁漆

Quick-drying enamels: Packed in 1, 1/2, 1/4-lb. &amp; 1 gallon tins.

調合漆  
厚 漆

Ready mixed paints: Packed in 1, 1/2, 1/4-gallon tins. Paste Paints: Packed in 28 lb. buckets.

氯酸鉀

Potassium Chlorate,  $KClO_3$ , Purity—99.8% up.

純度: 99.8%以上

Packed in 50 kg. wooden cases lined with 2-ply kraft-paper.

赤 磷

Red Phosphorus, Amorphous, P, Purity—95/96% and 98% up.

純度: 95/96%及98%以上

Packed in 5 or 10-kg. tins or iron buckets, outside with wooden cases.

酸洗抗蝕劑

Rodine, Available ingredient not less than 25%.

Packed in 20-kg. iron drums.

純 鹼

Soda Ash, Total alkalinity, as  $Na_2CO_3$ , not less than 98% (dry base).

純度: 98%以上

Packed in 80-kg. cloth bags, outside with gunny bags.

醋酸鈉

Sodium Acetate,  $NaC_2H_3O_2 \cdot 3H_2O$ .

小蘇打

Sodium Bicarbonate,  $NaHCO_3$ , Industrial use, Purity—99% up.

工業用, 純度: 99%以上

Packed in 50-kg. cloth bags, outside with gunny bags.

亞硝酸鈉

Sodium Nitrite  $NaNO_2$ , Purity—98% up.

純度: 98%

矽酸鈉 (又名水玻璃)

波美: 40 及 56 度

氟矽化鈉

純度: 98%以上

無水硫酸鈉

純度: 99%以上

硫化鈉 (即硫化碱)

純度: 60-62%及63.5%以上

固體及片狀。

硬脂酸 雙壓

燃點: 攝氏 52 度

碳化煤

氧化鋅

純度: 99%以上

氫氧化鋁

英國藥典 1949 版

次炭酸鈉

英國藥典 1953 年版

次沒食子酸鈉

英國藥典 1953 年版

次醇酸鈉

英國藥典 1949 年版

葡萄糖鈣

口服及注射用

乳酸鈣

粉狀及顆粒狀, 英國藥典 1953 年版。

蓖麻油

英國藥典 1953 年版

Sodium Silicate, Baume Degrees—40° and 56°.

Sodium Silicofluoride,  $Na_2SiF_6$ , Purity—98% up.

Packed in 50-kg. gunny bags.

Sodium Sulphate, Anhydrous,  $Na_2SO_4$ , Purity—99% up.

Packed in 125-kg. double gunny bags.

Sodium Sulphide,  $Na_2S$ ,  $Na_2S$  contents 60-62%, also 63.5% up. Solid fused, and also Flakes.

Packed in 50, 100 or 160-kg. iron drums.

Stearic Acid, Double pressed.

Melting point: 52°C.

Packed in 40-kg. wooden cases.

Sulfonated Coal, Softening value ton degree/cubic meter not less than 900.

Packed in 50-kg. wooden cases, lined with 2-ply kraftpaper.

Zinc Oxide,  $ZnO$ , Purity—99% up.

Packed in 50 or 100-kg. canvas bags lined with 2-ply paper bags.

Aluminium Hydroxide, B.P.C. 1949.

1. 1-lb. bottles.

2. 20-kg. plywood drums.

Bismuth Subcarbonate, B.P. 1953.

1. 1-lb. carton.

2. 5-kg. tins.

3. 28-lb. tins.

Bismuth Subgallate, B.P. 1953.

1. 1-lb. carton.

2. 5-kg. tins.

3. 28-lb. tins.

Bismuth Subnitrate, B.P.C. 1949.

1. 1-lb. carton.

2. 5-kg. tins.

3. 28-lb. tins.

Calcium Gluconate, oral and injectable.

Packed in 50-kg. wooden barrels.

Calcium Lactate, B.P. 1953, Powder and Granulars.

1. 25-kg. cloth bags, 2 bags to a wooden case.

2. 50-kg. plywood kegs.

3. 1-lb. cartons, 112 cartons to a wooden case.

Castor Oil, B.P. 1953.

1. 180-kg. iron drums.

2. 20-kg. tins.

鹽酸麻黃素  
英國藥典 1953 年版

Ephedrine Hydrochloride, B.P. 1953.  
1. Powder 80 mesh.  
2. Crystals.

Packed in:—  
1. 1-lb. bottles, 30 bottles to a wooden case.  
2. 1-kg. tins, 30 tins to a wooden case.  
3. 24-kg. tins, 12 tins to a wooden case.  
4. 5-kg. tins, 6 tins to a wooden case.  
5. 1-oz. bottle packing & bulk packing in tins of 28, 56, 112 lbs. and 50 kgs. also available.

蘇打粉  
粉狀，英國藥典 1953 年版

Extract Belladonnae, B.P. 1953, Powder form.  
1. 10-kg. tins, 4 tins to a wooden case.  
2. 1-kg. bottles, 20 bottles to a wooden case.

硫脲脂  
英國藥典 1953 年版

Ichthammol, B.P. 1953, Synthesized from Vegetable Oil,  
1. 1-lb. bottles, 28-30 bottles to a wooden case.  
2. 1-kg. bottles, 25 bottles to a wooden case.  
3. 50-kg. jars.

胰酶素  
英國藥典 1953 年版

Pancreatin, B.P. 1953,  
Packed in 1-lb. bottles, 20 bottles to a wooden case.

胃蛋白酶  
英國藥典 1953 年版

Pepsin 1:2500, B.P. 1953,  
Packed in 1-lb. bottles, 20 bottles to a wooden case.

路丁粉

Rutin, packed in 1-kg. bags.

香港代理處：華潤公司  
Hongkong Agency: CHINA RESOURCES CO.

中國機械進口公司經營  
EXPORTER: CHINA NATIONAL MACHINERY IMPORT CORP.

機械  
MACHINERY

1. 通用機械 General Machinery

油壓千斤頂 Centrifugal Pump  
離心水泵 Hydraulic Jack

齒輪油泵 Gear Oil Pump  
水泵 Water Pump

2. 工具機床 Machine Tools

A. 金屬切削機  
床類

Metal Cutting Machines

Turret Lathe  
All General Lathe  
Vertical Boring & Turning Machine  
Multi-tool Semi-automatic Lathe  
Upright Drilling Machine  
Universal Vertical Drilling Machine  
Portable Swing Drilling Machine  
Radial Drilling Machine  
Horizontal Boring Machine  
Gear Shaping Machine  
Gear Hobbing Machine  
Cylindrical Grinding Machine  
Surface Grinding Machine  
Tools Cutter Grinding Machine  
Grinder  
Universal Milling Machine  
Horizontal Milling Machine  
Double-Housing Planer  
Shaping Machine  
Hack Saw Machine

B. 鍛壓設備

Forging & Pressing Machine

3. 礦山機械 Mining Machinery

單筒卷揚機 Single Drum Winch  
卷揚機 Winch  
刮板運輸機 Scraper Chain Conveyor  
蒸汽兩用錘 Pneumatic and Steam Hammer  
翻魚剪床 Stearing Machine

雙柱封閉式 Double Column Crank Press

摩擦壓力機 Friction Screw Press

C. 金屬切削工 Metal Cutting Tool

鑽頭 Drill  
絲錐 Stock  
板牙 Die  
銼刀 Milling Cutter  
銼刀 Reamer  
齒輪滾刀 Involute Gear Hobs  
齒輪銼刀 Involute Gear Cutter

D. 研磨工具 Grinding Tools

Grinding Wheel  
油石 Oil Stone  
金鋼砂 Emery

E. 機床附件

三爪卡盤 Universal Chuck  
四爪卡盤 Independent Chuck  
平口鉗 Vise

F. 量具 Measuring Tool

塞規 Plug Gauge  
卡尺 Shap Gauge  
卡尺 Caliper  
鋼尺 Steel Rule

氣動裝岩機 Pneumatic Hammer Drill

顎式破碎機 Jaw Crusher

鍛針機 Drilling Head Forging Machine

圓盤粉碎機 Laboratory Disc Crusher

(實驗室用)



縫口機 Sewing Machine  
縫邊機 Hemming Machine

打包機 Baling Machine  
打包機油泵 Baling Oil Pump

## 2. 針織機 Knitting Machine

汗布機 Plain Fabric Knitting Machine (Daiman)  
棉毛織機 Interlock Fabric Knitting Machine  
複式汗絨針織機 Spring Needle Knitting Machine  
高筒提花針織機 Automatic Fancy Hosiery Knitting Machine (With High Needle Cylinder)  
電動織絨機 Automatic Hosiery Knitting Machine  
電動絲口羅紋機 Automatic Rib Top Knitting Machine  
電動領口羅紋機 Automatic Rib Neck Knitting Machine  
電動袖口羅紋機 Automatic Rib Cuff Knitting Machine

結絨頭機 Lockatch Loop  
蒸汽壓絨機 Steam Press for Hosiery  
蒸汽燙絨架 Steam Drying Board & Frame for Hosiery  
拉毛機 Raising Machine  
離心力脫水機 Centrifugal Hydro-extractor  
紗線絲光機 Yarn Mercerizing Machine  
蒸汽熱光機 Steam Calendering Machine  
紅木錠搖紗機 Bottle Bobbin Winding Machine  
寶塔錠倒線機 Conic Tube Traverse Winder  
轉線機 Bamboo Hexagon Traverse Machine  
針織計量表 Knitting Fabric Counter

## 3. 工業縫紉機 Industrial Sewing Machine

高速工業用縫紉機 High Speed Industrial Sewing Machine  
縫紉粉袋用縫紉機 Flour-bag Cap Sewing Machine  
毛絨縫邊用縫紉機 Woollen Blanket Overriding Sewing Machine

縫紉袋用縫 Gunny-bag Cap Sewing Machine  
三線袋口縫 Three-thread Overlock Machine

## 4. 木工機械 Wood-Working Machine

圓鋸機 Universal Circular Saw Machine  
帶鋸 Universal Band Saw Machine  
木工排鋸機 Wood-Working Gang Saw Machine  
萬能鋸木機 Universal Radial Arm Power Saw Machine

方桿式電動板機 Hand-planing Machine  
木工車床 Wood-turning Lathe  
擺鋸 Hanging Oscillating Circular Saw  
多面刨木機 Multi-side Planing Machine

## 5. 印刷及文化用機械 Printing Press Machinery

32吋單捲筒八板輪轉印報機 Uni-reel 8-page Newspaper Rotary Press (Model RP 1-32)  
64吋單捲筒十六板輪轉印報機 Uni-reel 16-page Newspaper Rotary Press (Model RP 1-64)  
剉鉛版機 Automatic Boring Machine (Autoshaver) (Model RF-14)  
鋅鉛版機 Stereo-Plate Casting Machine, Model RD-14  
溶鉛爐連泵浦 Melting Oven with Pump, Model RN-14

500噸壓絨板機 Hydraulic Matrix Moulding Press  
全張自動切紙機 Automatic Paper Cutting Machine, Model PC-50  
對開切紙機 Paper Cutting Machine, Model PC-36  
三面切紙機 Three-knife Book Trimming Machine, (Model BT)  
訂書機 Wire Stitching Machine, Model WSP  
鑄字機 Type Casting Machine, Model TCL

雙連轉印機 Two-Revolution Press, Model TRP  
式凸版機 Platen Press, Model PP-14  
方箱印刷機 Platen Press, Model PP-10 (for Treadle Drive)  
大二號元盤機 Platen Press, Model PP-16  
三色凸版機 Cylinder Job Press, Model CIQ  
四開箱印機

對開膠板機 Single Colour Offset Machine, Model-OHC  
(鏈式) Lifting Truck, Model LT  
拖紙機 Offset Proof and Transfer Press, Model OPHand OFF.  
全張膠板打機 Zinc Plate Grinding Machine  
全張磨字機  
鑄字盤 Type Casting Case

## 6. 食品工業用機械 Food-Stuff Industry Machinery

A. 餅乾機 Biscuit Bakery Equipment  
混麵機 Biscuit Dough Mixer  
皮子機 Biscuit Meal Sheeter  
印模機 Biscuit Moulding Press  
烘爐 Circulated Turbo-fan Oven.

B. 銨壓縮機 Ammonia Compressor  
冷藏機 Ammonia Self-contained Refrigerating Machine  
銨壓縮機 Ammonia Compressor

C. 榨油機 Oil Expelling Machine  
篩籽機 Seed Sieving Machine  
六角篩 Hexagonal Sieve  
吸塵篩 Suction Sieve  
滾筒打篩機 Roller Sieving Machine  
制殼磨料機 Unshelling and Grinding Machine

滾筒軟料機 Roller Softener  
螺旋式榨油機 Screw Type Oil Expeller  
濾油機 Oil Filter  
碎餅機 Cake Breaker  
油泵 Oil Pump

D. 製捲煙機械 Cigarette Making Machine  
高速自動捲煙機 High Speed Cigarette Making Machine  
切煙機 Tobacco Cutting Machine  
折菸煙機 Stalk Crusher (or Stem Flattening Machine)  
紙盒機 Cigarette Carton Machine  
自動包裝機 Automatic Wrapping Machine  
磨刀機 Knife Grinder

## 7. 日用品製造機械 Industrial Machinery for Making Various Dairy Commodities

A. 製牙膏機 Tooth Paste Making Machine  
溶鉛鍋 Lead-melting Furnace  
鉛板車 Lead Sheet Mold  
軋板車 Lead Sheet Rolling Mill  
落片機 Lead Sheet Stamping Machine

烘熟機 Tobacco Drying and Cooling Machine  
廢料機 Tobacco Recovering Machine for Waste Cigarette  
煙葉潤濕機 Leaf Moistening Machine  
煙葉烘乾機 Leaf Drying Machine  
加香料機 Flavour Mixing Machine

E. 麵粉機器 Flour Mill Machinery  
(i) 淨麥部份 (i) Wheat Cleaning Department:  
頭道麥篩 Receiving Separator No.2  
二道麥篩 Milling Separator No. 2  
三道麥篩 Separator No. 2  
打麥篩 Scourer No. 4  
刷麥機 Horizontal Brush Machine  
篩子機 Cockle Machine, 9 cylinders

(ii) 磨粉部份 (ii) Flour Mill Department:  
複式磨子機 Double Roller Mills 9" x 30"  
複式磨子機 Double Roller Mills 9" x 36"  
平篩 Plane Sifter No. 250  
圓篩 Differential Reels  
煉粉機 Purifier 40" x 76"  
煉皮機 Bran Duster  
麥磅 Wheat Scale

(iii) 打包部份 (iii) Packing Department:  
麵粉打包機 Flour Packer  
鐵皮打包機 Bran Packer  
鐵粉箱 Duster Collector  
鐵風箱 Steel Plate Exhauster No. 35  
鏈袋口機 Bag Sealing Machine

銑管機 Tube Punching Machine  
軟管纏繞機 Tube Screwing Machine  
底子印刷機 Tube Printing Machine  
三色印刷機 Three-colour Tube Printing Machine  
夾層拌膠機 Paste Storage Tank

混合池 Mixing Tank  
貯槽池研磨 Grinding Tank  
機  
齒輪泵 Gear Pump  
牙膏泵 Paste Pump  
裝管機 Paste Filling Machine  
B. 製皂機械 Machinery for Soap Making Industry  
溶油池 Fats Dissolving Tank

溶碱池 Soda Dissolving Tank  
離心泵 Centrifugal Pump  
煮皂鍋 Soap Heater  
肥皂泵 Soap Pump  
存皂池 Soap Storage Tank  
夾層拌皂鍋 Soap Mixer  
肥皂冷却機 Soap Cooling Machine  
切皂機 Soap Cutting Machine  
打印機 Trade Mark Stamper

## 8. 其他機械 Miscellaneous

A. 製紙盒機械 Cardboard Box Making Equipment:  
瓦楞機 Board Corrugating Machine  
襯紙機 Board Lining Machine  
胖紙機 (壓線機) Groove Press  
分紙機 Paper Cutter  
四聯刀鋼紙機 4-knife Paper Cutter  
沿絲釘盒機 Paper Box Stitching Machine  
割縫機 Line Press  
切格捲紙機 Row Cutter  
木台側刀 Wood Platform Trimmer

B. 搪瓷機器 Complete Equipment for Manufacturing Enamel-ware.  
沖床 Punch  
雙座風床 Drawing Press  
切片機 Shear  
呀光機 Spinning Machine  
台上切捲車 Bench Roller  
磨粉車 Grinder for Grinding Enamel Powder  
磨石粉車 Stone Grinder with Sieves for Grinding Granite.  
磨餅機 Crusher for Crushing Antimony  
調合機 Mixer  
滾機捲邊車 Folding Machine

C. 製安全別針機器 Safety-pin Making Machinery  
保險別針拔 Wire Straightening Cutting & Sharpening Machine.  
直邊尖車 Lock Making Press  
保險別針沖頭車 Wire Coiling Machine  
保險別針機 Lock Gripping Press  
保險別針捲邊車

D. 製造鐵鈕機 Stud Making Machinery  
機  
雄片落料翻 For Male Part of Stud, Punch  
邊車 Press for Cutting.  
雄片沖條車 For Male Part of Stud, Press  
雌片沖條車 For Female Part of Stud, Press  
雌片落料翻 For Female Part of Stud, Punch Press  
鐵鈕鋼絲彈 Wire Spring Making Machine  
黃車 Vertical Air Compressor  
立式空氣壓箱機  
鐵鈕機沖模 Dies

E. 輪胎機械 Rubber Tyre Industry Machinery  
輪胎翻修機 Rubber Tyre Reconditioned Equipment  
橡膠混合機 Rubber Mixer  
電木原料混 Filler Mixer  
合機  
油泵灌胎機 Oil Pump  
胎面壓出機 Surface Press  
局部活動型 Portable Local Repairer  
補胎機 Bicycle Tyre Repairer  
自行車胎壓出機

F. 裝釘機 Nail Making Machinery  
拉絲機 Wire Drawing Machine  
各種釘車 Nail Making Machine  
滾亮車 Nail Tumbler Machine

G. 製木牙螺絲機 Wood Screw Making Machine

H. 水泥包壓機 Cement Packing Machine

I. 真空製磚機 Vacuum Brick Making Machine

J. 製大頭針機 Paper Pin Making Machine

K. 製玻璃杯及瓶機械 Glass Making Machine  
自動壓杯機 Automatic Mould for Making Drinking Glass  
半自動壓杯機 Semi-automatic Mould for Making Drinking Glass  
三鐵碗吹瓶機 Bottle Blowing Machine with 3 moulds  
L. 木螺絲機 Wood Screw Making Machinery

M. 鞋釘機 Blue Cut Tack Making Machinery  
N. 鋼筆刻名機 Pen Engraving Instrument  
O. 噴花槍 Spraying Gun  
P. 蓄電池 Storage Battery  
Q. 壓蔗機 Sugar Cane Press

香港代理處：華潤公司  
Hongkong Agency: CHINA RESOURCES CO.



## 中國儀器進口公司經售

EXPORTER: CHINA NATIONAL INSTRUMENTS IMPORT CORPORATION

### 電工儀器

精密交流直流電流表，電壓表，三相電力表，單相功率因數表，過波積算器，高電阻計，線路試驗器，接地電阻測試器，校正用電位差計，十進式電容箱，十進式高週波電阻箱等。

### 電話機

自動式及共電式。

### 無線電用品

收音機，電子管，管座，各種線圈，各種礦電器，扳動開關，耳機，揚聲器，擴音機，電烙鐵，繞線車，及各種其他無線電用品，無線電參攷書藉；普通電唱機，自動落片電唱機，唱頭芯子，長命唱針等。

### 電影器材及照相用品

16公厘有聲電影放映機，幻燈機，炭精棒，照相紙，鏡箱等。

### 實驗室用儀器

實驗室用玻璃器皿，瓷器皿，扭力天平，顯微鏡，溫度計，比重計，溫度計，變壓表，及其他儀器。

### 各類示教儀器

各種物理儀器，化學儀器，數學模型；生物模型，標本，切片；生物器械；人體生理，病理模型，解剖學切片，地質地理模型；礦物標本；金屬與合金標本等。

### Electrical Instruments

Precision AC/DC ammeters, voltmeters, Three-phase wattmeters, Single-phase power factor meters, Cycle counter, High resistance tester, Fault location test sets, Earth tester, Potentiometer for calibration, Decade capacitance box, Decade high frequency resistance box, etc.

### Telephone Sets

Automatic type and common battery type.

### Radio & Accessories

Radio receiver, Radio tubes, Tube sockets, Coils, Condensers, Toggle switches, Earphone, Loudspeaker, Amplifier, Soldering iron, Coil winder, and other various radio accessories; Radio reference books, Record player, Automatic record changer, Magnet pick-up, Long life needle, etc.

### Cinematographic & Photographic Equipments

16 mm Sound film projector, Still projector, Carbon rods (arc-light), Photographic papers, camera outfit, etc.

### Laboratory Instruments & Apparatus

Glassware, Porcelainware, Torsion balance, Microscopes, Psychrometers, Hydrometers, Pyrometers, Thermometers, and other instruments.

### Educational Instruments

Physical laboratory apparatus, Chemical laboratory apparatus, Mathematical models; Biological models, specimens and slides; Biological apparatus; Physiological, Pathological models and slides; Geological and geographical models; Rock and mineral collections; Metals and metal alloy models, etc.

**繪圖儀器，計算機，打字機等**

套裝精密繪圖儀器，三用圖規，三棱尺，雲形規，三角板，量角規，及各種其他繪圖儀器；求積儀，計算機，中文打字機及中文打字機用油等。

**Drawing Instruments, Calculator, Typewriter, Etc.**

Precision drawing instruments in sets, Combination compasses, Triangular scales, French curves, Set squares, Protractors, and other various drawing instruments; Planimeter, Calculator, Chinese typewriters and Inks for Chinese typewriters, etc.

**工程儀器**

各種流量計，各種紡織工業儀器，二氧化碳分析器等。

**Engineering Instruments**

Flowmeters, Textile industry instruments, Carbon dioxide analyzer, etc.


香港代理處：華潤公司

Hongkong Agency: CHINA RESOURCES CO.

表內未能詳盡列入之項目，請洽詢我公司當即詳告。  
Should there be any requirement for items other than is mentioned in this list, please contact us for further information.

CODE : 6EM - 1003

普通車床  
ALL GEARED LATHE



中國機械進口公司經售

Exported by CHINA NATIONAL MACHINERY IMPORT CORPORATION

香港代理處：華潤公司

Hong Kong Agency: CHINA RESOURCES CO.


BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

CODE: 6EM-1011

Capacity	
Height of centers, mm ... ..	200
Maximum distance between centers, mm ... ..	750; 1000; 1500; 2000
Bar capacity, mm ... ..	37
Maximum swing over cross slide, mm ... ..	210
Maximum swing over bed ways, mm ... ..	400
Maximum length of turning (according to distance between centers), mm ... ..	650; 900; 1400; 1900
Threads that can be cut:	1—192
Metric, pitch in mm ... ..	24—2
English, threads per inch ... ..	0.5—48
Module ... ..	96—1
Diametral pitch ... ..	
Carriage	
Maximum travel (power or manual feed), mm:	
longitudinal (according to distance between centers) ... ..	650; 900; 1400; 1900
cross ... ..	280
Distance from tool bottom to center line, mm ... ..	25
Maximum swivel of top slide, deg ... ..	± 45
Spindle	
Diameter of hole in spindle, mm ... ..	38
Taper hole in spindle ... ..	Morse No. 5
Tailstock	
Taper hole in spindle ... ..	Morse No. 4
Maximum travel of spindle, mm ... ..	150
Setover on side, mm ... ..	± 15
Speeds and Feeds	
Number of spindle speeds:	21
forward ... ..	12
reverse ... ..	
Range of spindle speeds, r. p. m.:	
forward ... ..	11.5—1200
reverse ... ..	18—1520
Number of longitudinal and cross feeds ... ..	35
Range of feeds, mm per revolution of spindle:	
longitudinal ... ..	0.08—1.59
cross ... ..	0.027—0.52
Drive	
220/380 volt, 3 phase, 50 cycle A. C. motors:	
Main drive:	7
power, kw ... ..	1440
speed, r. p. m. ... ..	
Coolant pump:	0.125
power, kw ... ..	2850
speed, r. p. m. ... ..	
Space Occupied	
Overall length (according to distance between centers), mm ... ..	2400; 2650; 3180; 3680
Overall width, mm ... ..	1580
Height of machine, mm ... ..	1210
Weight	
Net weight (according to distance between centers), kg ... approx.	1930; 2010; 2100; 2280

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

## 六角車床 TURRET LATHE




中國機械進口公司經售  
Exported by CHINA NATIONAL MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

CODE: 6EM-1012

Capacity	
Height of centers, mm	210
Distance, end of spindle to turret face, mm:	
minimum	260
maximum	1177
Maximum swing, mm:	
over carriage	420
over cross slide	350
over bed ways	440
Hexagon Turret	
Total longitudinal travel (by power and manually), mm	917
Carriage and Cross Slide	
Total longitudinal travel of carriage (by power and manually), mm	1012
Total cross travel of slide, mm	259
Speeds and Feeds	
Number of spindle speeds	12
Range of spindle speeds, r. p. m.:	
forward...	44—1000
reverse	48—1094
Number of turret, carriage and cross slide feeds	16
Range of turret and carriage longitudinal feeds, mm per revolution of spindle	0.07—2.29
Range of cross slide feeds, mm per revolution of spindle	0.03—1.00
Drive	
220/380 volt, 3 phase, 50 cycle A. C. motor:	
power, kw	10
speed, r. p. m.	1500
Space Occupied	
Floor space, mm	3200 x 1780
Height of machine, mm	1450
Weight	
Net weight, kg	approx. 2980

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

## 六角車床 TURRET LATHE




中國機械進口公司經售  
Exported by CHINA NATIONAL MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

Centre height...	115 mm
Distance, spindle nose to turret ...	90-400 mm
Spindle hole, diameter ...	26 mm.
Maximum size of bar to be turned:	
Circular diameter ...	25 mm
Square... ..	18 mm
Hexagonal ...	21 mm
Maximum length to be turned ...	150 mm
Maximum chucking diameter	
Swing over carriage ...	250 mm
Swing over bed ...	300 mm
Maximum longitudinal traverse of turret ...	330 mm
No. of spindle speeds ...	6
Range of spindle speeds ...	140-1380 rpm.
No. of longitudinal feeds of turret ...	4
Range of longitudinal feeds of turret per revolution of spindle ...	0.06-0.25 mm.
Space required (L x W x H) ...	1815 x 740 x 1290
Nett weight approximately ...	900 kg.
Electric drive motor, A. C. 3ø, 50 c. 2.2 kw. 1450 rpm and 220/380 volts supply.	

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE. 6EM-1013

## 牛頭鉋床 CRANK SHAPER



中國機械進口公司經售  
Exported by CHINA NATIONAL MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

## Capacity

Length of ram stroke, mm:	
Minimum ... ..	95
Maximum ... ..	650
Distance from lower edge of ram to table, mm:	
Minimum ... ..	65
Maximum ... ..	370
Maximum distance from tool bottom to bed, mm ... ..	700

## Table

Working surface of table, mm:	
Top ... ..	550 × 450
Side ... ..	450 × 400
Saddle of table ... ..	450 × 400
Maximum table traverse, mm:	
Horizontal (power and hand) ... ..	600
Vertical (by hand) ... ..	300

## Ram and Tool Head

Maximum adjustment of ram (each side of center), mm ... ..	± 250
Maximum swivel of tool holder (each side of center) ... ..	± 20°
Maximum size of tool shank, mm ... ..	20 × 30
Maximum vertical travel of tool slide (by hand), mm ... ..	175
Maximum swivel of tool head (each side of center) ... ..	± 60°
Note: ± 60° swivel is allowed when clearance between tool head and bed guides is not less than 10 mm. In all other cases swivel of ± 20° is allowed.	

## Speeds and Feeds

Number of ram double strokes per minute ... ..	12.5; 17.9; 25; 36.5; 52.5; 73
Table horizontal feeds, mm per double stroke of ram:	
Minimum (per 1 tooth of ratchet) ... ..	0.33
Maximum (per 10 teeth of ratchet) ... ..	3.33

## Drive

220/380 volt, 3 phase, 50 cycle A. C. motor:	
Power, kw ... ..	3.5
Speed, r. p. m. ... ..	960

## Space Occupied

Floor space, mm ... ..	2500 × 1450
Height of machine, mm ... ..	1750

## Weight


Net weight, kg ... ..	approx. 1850
-----------------------	--------------

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: 6EM-1014

# 龍 門 鉋 床

## DOUBLE HOUSING PLANER



中國機械進口公司經售  
 Exported by CHINA NATIONAL MACHINERY IMPORT CORPORATION  
 香港代理處：華潤公司  
 Hong Kong Agency: CHINA RESOURCES CO.  
 BANK OF CHINA BUILDING  
 HONG KONG  
 CABLE ADDRESS: "CIRECO."

## Capacity

Distance from table to vertical tool head, mm:	
Minimum	0
Maximum	890
Distance between axes of vertical tool heads, mm:	
Minimum	290
Maximum	1470
Maximum extension of side and vertical tool heads, mm	265
Maximum width planned, mm	1000
Maximum height planned, mm	850
Maximum length planned, mm	3000
Maximum weight of work piece admitted, kg	5000

## Table

Working surface of table, mm	3000 x 900
Number of T-slots	5
Width of T-slots, mm	28
Distance between slots, mm	150

## Speeds and Feeds

Range of table cutting speeds, m/min.	5—75
Range of table return speeds, m/min.	15—75
Range of feeds of vertical tool heads per double stroke, mm:	
Vertical	0.125—6.2
Horizontal	0.5—25
Range of vertical feeds of side tool heads per double stroke, mm	0.25—11.5
Speed of rapid power traverse, m/min:	
Vertical heads:	
horizontal/vertical	2.33/0.585
Side heads: Vertical	1.07
Power travel of cross rail, m/min	0.5

## Drive

Number of electrical units	13
Motor-generator unit:	
Power of asynchronous motor, kw	40
Speed, r. p. m.	1460
Head feed motors: (3 pcs)	
Power, kw	1.7
Speed, r. p. m.	1430
Cross rail elevating motor:	
Power, kw	1.7
Speed, r. p. m.	1430
Cross rail clamping motor:	
Power, kw	0.6
Speed, r. p. m.	1410

## Space Occupied

Floor space, mm	7200 x 3650
Height of machine, mm	2680

## Weight


Net weight, kg	approx. 20500
----------------	---------------

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: 6EM-1019

# 普通車床


## ALL GEARED LATHE



中國機械進口公司經售  
 Exported by CHINA NATIONAL MACHINERY IMPORT CORPORATION  
 香港代理處：華潤公司  
 Hong Kong Agency: CHINA RESOURCES CO.  
 BANK OF CHINA BUILDING  
 HONG KONG  
 CABLE ADDRESS: "CIRECO."

CODE: 6EM-1021

# 普通車床 ALL GEARED LATHE



Capacity	
Height of centers, mm	160
Maximum distance between centers, mm	750
Bar capacity, mm	29
Swing over cross slide, mm	175
Swing over bed ways, mm	320
Threads that can be cut:	
Metric, pitch in mm	0.5—9
English, threads per inch	38—2
Module	0.5—9
Carriage	
Maximum travel (power or manual feed), mm:	
longitudinal	850
cross	210
Distance from tool bottom to center line, mm	20
Maximum distance from center line to the face of tool holder, mm	185
Maximum size of tool, mm	20 X 20
Spindle	
Diameter of hole in spindle, mm	30
Taper hole in spindle	Morse No. 5
Tailstock	
Taper hole in spindle	Morse No. 4
Maximum travel of spindle, mm	95
Setover on side, mm	± 10
Speeds and Feeds	
Number of spindle speeds (forward and reverse)	12
Range of spindle speeds, r. p. m.	44—1980
No. of feeds of slide, longitudinal and cross	140
Range of feeds of slide mm per revolution of spindle:	
longitudinal	0.06—3.34
cross	0.044—2.47
Drive	
220/380 volt, 3 phase, 50 cycle A. C. motors:	
Main drive:	
power, kw	4.5
speed, r. p. m.	1440
Coolant pump:	
power, kw	0.125
speed, r. p. m.	2850
Lubricating pump:	
power, kw	0.125
speed, r. p. m.	2850
Space Occupied	
Floor space, mm	2355 X 852
Height of machine, mm	1255
Weight	
Net weight, kg	approx. 1950

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

中國機械進口公司經售  
Exported by CHINA NATIONAL MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CINECO."




Height of center	200 mm
Distance between centers	1000 mm
Maximum turning diameter:	
round rod	37 mm
swing over carriage	210 mm
swing over bed	410 mm
Maximum turning length	900 mm
Thread cutting:	
metric threads, pitch	1—192 mm
whitworth threads, t.p.i.	24—2
module threads, M	0.25—48
UP threads, DP...	96—1
Maximum traverse of carriage (mechanically or manually):	
longitudinal	900 mm
cross	280 mm
Height between tool supporting surface to center line	23 mm
Maximum traverse of tool post	100 mm
Maximum swivel of tool post	45°
Diameter of spindle bore	38 mm
Taper of spindle bore	Morse No. 5
Taper of center sleeve	Morse No. 4
Maximum traverse of center sleeve	150 mm
Maximum cross traverse of tailstock	15
No. of spindle speeds (normal/reverse)	18/9
Range of spindle speeds:	
Normal	12—600 rpm.
reverse	18—760 rpm.
No. of longitudinal and cross feeds of carriage	35
Range of feed of carriage per revolution of spindle:	
longitudinal	0.082—1.59 mm
cross	0.27—0.522 mm
Electric motor (3 phase A.C.) power/speed	4.5/1500 kw/rpm.
Overall dimensions (L x W x H)	2650x1580 x 1220
Nett weight approx.	2240 kg.
Electric drive equipments includes:	
1 main drive motor of 4.5 kw and 1500 rpm., AC 3 φ, 50 cycle, 220/380 v.	

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: 6EM-1025

## 半自動多刀車床 MULTI-TOOL SEMIAUTOMATIC LATHE




中國機械進口公司經售  
Exported by CHINA NATIONAL MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
HONG KONG Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

Center height...	200 mm
Distance between centers (min./max.)...	200/500 mm
Maximum distance from spindle nose to center of tailstock...	580 mm
Maximum turning diameter:	
for bar...	48 mm
swing over bed...	410 mm
swing over carriage...	300 mm
Maximum turning length (two cutters)...	460 mm
Maximum longitudinal traverse of carriage:	
mechanically (turning)...	250 mm
manually (adjusting)...	325 mm
Maximum cross traverse of rear tool post:	
mechanically (turning)/manually (adjusting)...	235/225 mm
Maximum traverse of center socket...	165 mm
Spindle speeds: ...	40, 52, 65, 84, 107, 129, 153, 187, 240, 310, 388, 500, rpm.
Longitudinal feed of carriage per 1 revolution of spindle:	
0.12, 0.17, 0.23, 0.34, 0.49, 0.71, 0.97, 0.38, mm.	
No. of cross feeds per each longitudinal feed. ...	12
Range of cross feeds of rear tool post per 1 revolution of spindle:.....0.16—2.37 mm.	
3 phase A. C. Motors:	
for main driving: power/speed ...	10/1455 kw/rpm.
for rapid adjustment at carriage: power/speed ...	1/1425 kw/rpm.
for coolant pump: power/speed ...	0.15/2800 kw/rpm.
Overall dimensions (L x W x H) ...	2200 x 1700 x 1240 mm.
Net weight ...	apprcx. 3000 kg.

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: 6EM-1026

## 單柱立式車床 VERTICAL BORING MILL




中國機械進口公司經售  
Exported by CHINA NATIONAL MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

Diameter of table	1030 mm.
Distance between center of table and surface of column	625 mm.
Maximum turning diameter:	
with vertical head	1250 mm.
with side tool head	1120 mm.
Boring diameter (by rotary tool post or vertical tool head) minimum/maximum	120/1250 mm.
Maximum height of workpiece	1000 mm.
Maximum weight of workpiece	2000 mm.
Turning length by side tool head:	
on working table	730 mm.
outside working table	960 mm.
Diameter of workpiece to be clamped,	
minimum/maximum	70/900 mm.
Maximum traverse of vertical tool head (mechanically or manually),	
horizontal/vertical	750/700 mm.
Maximum swivel of vertical tool head	45°
Maximum traverse of side tool head (mechanically or manually),	
horizontal/vertical	600/960 mm.
Spindle bore of table	150 mm.
No. of table speeds	12
Range of table speeds	7.5 - 150 rpm.
No. of feeds of vertical tool head and side tool head	8
Feed per revolution of table	0.23 - 8.4 mm.
Rapid traverse of vertical tool head & side tool head	2 m/min.
Rapid elevating speed of rail	0.5 m/min.
3 $\phi$ A. C. motor:	
for main drive: output/speed	22/1460 kw/rpm.
for rapid adjustment: output/speed	1.7/930 kw/rpm.
Overall dimensions (L x W x H)	2350 x 2185 x 3815 mm.
Net weight approx.	10000 kg.

N.D.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: 6EM - 1031

## 插 齒 機 GEAR SHAPER



中國機械進口公司經售  
Exported by CHINA NATIONAL MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

CODE : 6EM - 1034

**Capacity**

Distance between work spindle face and cutter shoulder at maximum eccentricity of crank pin, mm:

maximum	160
minimum	35
Module that can be cut, mm	2—6
External diameter of spur and helical gears, mm:	
maximum	462
minimum	20
Maximum external diameter of work when cutting internal teeth, mm	350
Maximum face width that can be cut, mm...	105
Maximum helix angle for helical gears...	23°

**Cutter Saddle**

Maximum length of cutter spindle stroke, mm	125
Maximum longitudinal cutter saddle traverse, mm	510

**Work Spindle Apron**

Maximum relieving movement of apron, mm	0.5
Diameter of work spindle flange, mm	240
Maximum distance between centers of work and cutter, mm	350

**Speeds and Feeds**

Number of cutter strokes per minute	125; 179; 253; 359
Rotary feeds, mm per stroke of cutter...	0.17; 0.21; 0.24; 0.30; 0.35; 0.44

**Drive**

220/380 volt, 3 phase, 50 cycle A. C. motors:

Main drive:	
power, kw	2.8
speed, r. p. m.	1437
Rapid rotation of work spindle:	
power, kw	0.6
speed, r. p. m.	1440
Coolant pump:	
power, kw	0.25
speed, r. p. m.	2820

**Space Occupied**

Floor space, mm	1750 x 1270
Height of machine, mm...	2060


**Weight**

Net weight, kg	approx. 3530
----------------	--------------

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

## 萬 能 銑 床

### UNIVERSAL MILLING MACHINE




中國機械進口公司經售  
 Exported by CHINA NATIONAL MACHINERY IMPORT CORPORATION  
 香港代理處：華潤公司  
 Hong Kong Agency: CHINA RESOURCES CO.  
 BANK OF CHINA BUILDING  
 HONG KONG  
 CABLE ADDRESS: "CIRECO."

CODE: RM - 2001

Capacity	
Working surface of table, mm	1000 x 250
Distance, center line of spindle to top of table, mm:	
Minimum	30
Maximum	350
Distance, face of column to center line of table, mm:	
Minimum	170
Maximum	370
Distance, center line of spindle to overarm, mm...	150
Maximum table travers, mm:	
Longitudinal	650
Cross	200
Vertical	350
Maximum table swivel	$\pm 45^\circ$
Speeds and Feeds	
Number of spindle speeds	16
Range of spindle speeds, r. p. m.	65—1800
Number of table feeds	16
Range of table feeds, mm/min.:	
Longitudinal	35—980
Cross	25—765
Vertical	12—380
Drive	
220/380 volt, 3 phase, 50 cycle A. C. motors:	
Main drive:	
Power, kw	4.5
Speed, r. p. m.	1450
Feed drive:	
Power, kw	1.7
Speed, r. p. m.	1430
Coolant pump:	
Power, kw	0.1
Speed, r. p. m.	2800
Space Occupied	
Floor space, mm	1800 x 1470
Height of machine, mm...	1590
Weight	
Net weight, kg	approx. 2100

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

**B-3 型 橡 口 織 襪 機**  
**AUTOMATIC HOSIERY MACHINE,**  
 FOR COLOUR STRIPED SOCKS WITH  
 ELASTIC TOP  
**MODEL B-3**



中國運輸機械進口公司經售  
 Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
 香港代理處：華潤公司  
 Hong Kong Agency: CHINA RESOURCES CO.  
 BANK OF CHINA BUILDING  
 HONG KONG  
 CABLE ADDRESS: "CIRECO."

Model B-3 differs from Model B-1 in such a way that it is provided with attachments for making colour striped hose with elastic top.

The colour stripe pattern is accomplished by means of a colour pattern drum and yarn changing fingers, it enables the knitting of a large variety of horizontal striped pattern. The colour pattern drum is mounted above the main pattern drum, latter being common to all Model B machines. For cutting the pattern yarns, an automatic cutter is fitted to the colour pattern drum.

The machine is arranged with six yarn changing fingers for patterns in horizontal stripes of five different colours.

An elastic lay-in attachment is provided for insertion of rubber yarns in elastic tops. These elastic tops insure comfort in wear and will fit snugly to the leg.

Model B-3 embodies our latest improvements and designs and is worthy of recommendation. Besides, it produces colour striped hose which is well in demand in various countries of the world.

#### Specifications :

##### Number of Needles :

Available in cylinder diameters and number of needles as follows:—

3½" with 160, 176 and 188 needles.

3¾" with 160, 176, 188 and 200 needles.

Power Required : 1/4 H. P.

Cylinder Speed : 200 - 220 rpm.

Drive Pulley : 7" dia. 3/4" width. Speed: 138-150 rpm.

Floor Space : Installation floor space 1' - 6" x 2' - 6"

Working space 2' - 6" x 5' - 0"

Production : Based on 8 working hours about 70 pairs of cotton socks.

Packing : In wooden case.


##### Shipping Specification:

Net weight 385 lbs. Gross weight 500 lbs. Measurement: 27" x 30" x 34".

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT-2002

## 棉毛織機 (又名雙面機) INTERLOCK KNITTING MACHINE



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

CODE: RT-2003

This machine is a multiple-feed, circular, latch-needle interlock stitch knitting machine of non-sinker type, designed for producing interlock fabrics in either plain colours or a wide range of horizontal stripes. With modification of its parts, it can produce towel fabrics. The planned body size comes right off the machine, eliminating the slitting and sewing of side seams.

Outstanding advantages of the machine are:—

#### SIMPLIFIED MAINTENANCE-ECONOMY IN SPACE

**Construction:** The machine features tripod construction; positive clutch; brass cut cylinder and dial; hardened needle cams for cylinder and dial; stationary bobbin stand; revolving take-up and cloth roll-up; fabric stop motion.

**Number of Feeds:** The machine is built in different cylinder diameters with corresponding number of feeds as follows:—  
14" - 14 feeds; 15" - 16 feeds; 16" - 16 feeds;  
17" - 18 feeds; 18" - 18 feeds; 19" - 20 feeds;  
20" - 20 feeds; 21" - 22 feeds.

**Gauge:** The cylinder and dial can be supplied in different gauges (number of needles per inch) to suit the counts of cotton yarn handled. For example, when using 20/1 cotton yarn, we recommend 17 needles per inch for fine quality fabrics and 13-14 needles per inch for second quality.

**Speed:** For 18" diameter machine, the cylinder speed is 18 revolutions per minute.

**Power required:** 3/4 HP in case of individual drive.  
3 HP for 6 machines in case of group drive.

**Output:** The output increases or decreases depending on the skill of the operator, gauge and diameter, count of yarn, etc. Average 280-440 ounces in 8 hours.

**Width of Fabric:** The width of fabric depends on the diameter of the machine, kind of material, count of yarn, etc. When using cotton of medium counts, we recommend diameter of machine as follows:—

<b>For Underwear:</b>						
Diameter of machine	17"	18"	19"	20"	21"	
Open width of fabric	32"	34"	36"	38"	40"	


<b>For slitting trousers:</b>						
Diameter of machine	19"	20"	21"	22"		
Size of trousers	32"	34"	36"	38"		

#### Data for 18" Diameter machine:

Installation floor space	3' 8" X 4' 4"
Working space required	5' 6" X 6' 6"
Net weight-880 lbs.	

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

## 複式汗絨針織機 (湯姆金機) SPRING NEEDLE KNITTING MACHINE



中國運輸機械進口公司經售  
Exported by: CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處: 華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

This machine is a multi-feed, circular spring needle knitting machine designed for producing cambric fabrics, common tissue or different weight of cotton flannel, and also plain colour imitation of camel hair fabrics. Equipped with additional pattern attachment, the machine can produce many different kinds of fancy knitted cloth. The machine is equipped with automatic take-up and rolling up of fabric as knit. Take up is suspended on ball bearing over the center of the cylinder and is constructed for variable production of fabric. Fabric stop motion is applied to each cylinder.

The machine can be arranged for individual or group drive. A positive clutch is provided on each cylinder facilitating starting of the machine.

Machines are built in two table sizes, A and B respectively, with two cylinders installed on the same table. Cylinders are available in two ranges, viz., for table size, A-16" to 20"; B-24" to 30". According to the cylinder diameters, 3 to 5 feeds are applied to each cylinder.

The gauge of the machine should be adapted to the kind of products.

We recommend cylinder gauges as follows:

PRODUCT	Cylinder Diameter Recommended	Cylinder Gauge	No. of Feeds Each Cylinder	Cotton Yarn Used
Tissue cloth	16"-20"	32, 34, 36, 40	4 or 5	65x1-405x1
Cotton flannel	24"-30"	20, 22, 24, 28	3	325x1-1005 /2x1

Outstanding advantage of the machine is its capability of producing a large variety of fabrics with finest quality as is not possible with ordinary knitting machines.

The output depends on the skill of the operator, gauge and diameter, counts or yarns, etc., and average is:

For tissue cloth-500 to 700 ounces in 8 hours;

For cotton flannel-2,000 to 2,800 ounces in 8 hours.


#### DATA OF SPRING NEEDLE MACHINE

Table Size	A	B
Cylinder Diameter	16" to 20"	24" to 30"
Working Space Required	4'0" x 8'6"	5'0" x 9'0"
Horse Power Required	1½ HP	2 HP
Cylinder Speed	70-80 RPM	60-65 RPM
Net Weight	2,240 lbs.	2,700 lbs.

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

COOE: RT - 2004

## 電動領口羅紋機 AUTOMATIC RIB NECK KNITTING MACHINE



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."



This machine is used for knitting rib necks of underweares, stockinetes or sweaters.

*Specification:-* Available in different cylinder diameters with number of needles as follows:-

6", 3 Shuttles, 320-540 needles

6½", 3 Shuttles, 320-540 needles

7", 4 Shuttles, 320-540 needles

*Power Required:-* 1/2 HP for single machine, 1 HP for 3 machines in group drive

*Cylinder Speed:-* 75-80 rpm.

*Weight:-* Nett: 110 kgs. approx.  
Gross: 150 kgs. approx.

*Floor Space:-* Space occupied 26" x 26"  
Working space required 4' x 5'


*Attendance:-* One person can operate 5-6 machines

*Production:-* Based on 10 working hours, 400-500 shi-liangs (12½-15½ kgs.) for 20s/2 yarn, and 300-500 shi-liangs for 42s/2 yarn.

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT-2005

紅木錠搖紗機  
BOTTLE BOBBIN WINDING MACHINE



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

CODE: RT - 2006

This machine is used for winding yarns in skeins or rewinding yarns in bamboo reels into bottle bobbin.

**Specification:-** 36 spindles, 40 spindles

**Power Required:-** 1 HP. for 36 spindles machine,  $1\frac{1}{2}$  HP. for 40 spindles machine; driven by an electric motor with a speed of 960 r. p. m.

**Speed:-**  
Spindles speed: 800-1000 rpm  
Driven pulley: 12"-12.3/8" diam.  
280-300 rpm  
Slow speed for winding from skeins and fast speed for rewinding from reels.

**Nett Weight:-** 800 kgs. for 36 spindles machine, 850 kgs. for 40 spindles machine.

**Floor Space:-** Space occupied:  
36 spindles machine 13' x 4'  
40 spindles machine 14' x 4'

Working space required:  
36 spindles machine 14' x 8'  
40 spindles machine 16' x 8'

**Production:-** In package of 3.75 kgs. per 10 working hours a day with 40 spindles, (For skein winding and rewinding)


Single yarn:  
50-60 for 6s., 8s.; 32-40 for 10s.  
20-30 for 20s; 12-14 for 32s;  
8-10 for 40s.

Twist yarn:  
30-40 for 32s; 24-34 for 42s;  
14-16 for 60s; 10-12 for 84s;  
8-9 for 100s.

**Advantages:-**  
1) Direct winding from skein to the bobbin  
2) Suitable for 2 wide range of yarn 6s.-100s.  
3) High production and low power consumption  
4) Non stop bobbin changing.

*N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.*

## 汗布機 (又名台木膏) BODY SIZE KNITTING MACHINE



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

CODE: RT - 2607

This machine is a multiple feed, circular, latch-needle knitting machine of non-sinker type, designed for production of plain fabrics in either plain colours or a wide range of horizontal stripes. With modification of its parts, it can produce net fabrics.

The planned body size of the underwear comes right off the machine, eliminating the slitting and sewing of side seams.

Outstanding advantages of the machine are:-

#### SIMPLIFIED MAINTENANCE—INCREASED PRODUCTION

**Main Features:-** The machine features tripod construction; positive clutch; brass cut cylinder; hardened needle cams; stationary bobbin stand; revolving take up and cloth roll up; fabric stop motion.

**Number of Feeds:-** The machine is available in different cylinder diameters with corresponding number of feeds as follows:-  
13"-26 feeds; 14"-28 feeds; 15"-30 feeds;  
16"-32 feeds; 17"-34 feeds; 18"-36 feeds;  
19"-38 feeds; 20"-40 feeds;

**Gauge:-** The cylinder can be supplied in different gauges (number of needles per inch) to suit the counts of cotton yarn handled. For common plain fabrics, 19-20 needles per inch is recommended.

**Speed:-** For 18" diameter machine, the cylinder speed is 22 revolutions per minute.

**Power required:-** 3.4 HP in case of individual drive.  
3 HP for six machines in case of group drive.

**Output:-** The output depends upon the skill of the operator, gauge and diameter, count of yarn, etc.

#### Average:-

When using 32/1 and 40/1 cotton yarns, 320-480 oz. in 8 hrs.  
When using 16/1 and 20/1 cotton yarns, 480-640 oz. in 8 hrs.

**Width of Fabric:-** The width of fabric depends on the diameter of the machine, kind of material, count of yarn, etc. When using cotton of medium counts, we recommend diameter of machine as follows:-

#### For Underwear:-

Diameter of machine:- 16" 17" 18" 19" 20"  
Open width of fabric:- 32" 34" 36" 38" 40"


#### Data for 18" Diameter Machine:-

Installation floor space 3' 8" x 4' 4"  
Working space required 5' 6" x 6' 6"  
Net weight 660 lbs.

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

縫襪頭機 (又名套口機)

LOCKSTITCH LOOPER



中國運輸機械進口公司經售

Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION

香港代理處：華潤公司

Hong Kong Agency: CHINA RESOURCES CO.

BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

This machine is used for looping toe-top hosiery or sleeves to knitted underwears.

*Specification:-* for toe-looping, looping points: 12, 14, 16, 18, 20, 22, 24, 26, 28, 30.

*Power Required:-* 1 HP for 12 machines

*Machine Speed:-* driving pulley 250-300 RPM

*Nett Weight:-* 80 kgs. approx

*Floor Space:-* Space occupied - 2' x 3'  
Working space required - 3' x 6'

*Attendance:-* 1 to 3 operators for each machine


*Production:-* for toe-looping, 1 worker can loop 40 doz. pairs heavy hosiery or 20 doz. pairs light hosiery; for sleeve looping 15 doz. underwears, production being based on 10 working hours.

*Advantages:-* Occupies little space, low power consumption, little labour required, high production capacity.  
Number of needles can be altered to suit fine or coarse knitted fabrics.  
Guaranteed free from yarn breakage or other defects with production of high quality.  
Can be arranged for treadle drive in case electric power is not available.

*N.B.-For improvement of the machine, we reserve the right to alter either the design or the specification.*

CODE: RT-2008

高筒提花織襪機  
AUTOMATIC FANCY HOSIERY KNITTING MACHINE  
WITH HIGH NEEDLE CYLINDER



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

CODE: RT-2009

This machine is adapted for knitting all kinds of new fancy socks. There are five yarn-fingers for inter-knitting yarns of 5 colours. The latch ring opens automatically subsequent to the completion of sock.

**Specification:-** Available in cylinder diameter of 3-1/2" with 160, 176, 188 and 200 needles.

**Power Required:-** 1 HP for each machine

**Cylinder Speed:-** 200-220 RPM

**Weight:-** Nett 170 kgs. for each machine

**Floor Space:-** Space occupied-1'-6" x 2'-6"  
Working space required 2'-6" x 5'-0"


**Attendance:-** One operator can handle 2-3 machines

**Production:-** Based on every 10 working hours about 6 doz. pairs of socks

**Advantages:-** Low power consumption, high production capacity  
Suitable for knitting socks of mercerized cotton yarn or artificial silk.  
Welt can be knitted with any desired elasticity sole size and heel height can be adjusted by the chain.  
A wide range of patterns possible by simply adjusting the pattern wheel and jacks.

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

## 開式電力織襪機 AUTOMATIC HOSIERY KNITTING MACHINE MODEL K



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO,"

This machine is specially manufactured for knitting fashionable seamless stockings. The welt transfer and hosiery fashion are knitted automatically.

**Specification:-** The machine is available in different cylinder diameters and number of needles as follows:-  
 3" Diam. 96, 120, 140 needles for 6s and 20s counts yarn.  
 3½" Diam. 160, 176, 188, 200 needles for 32s/2 and 42s/2 counts yarn.  
 3¾" Diam. 220, 240, 260, 280 needles for 60s/2 and 84s/2 counts thread.

**Power Required:-** ½ HP for single machine, 5 HP for 12 machines in case of group drive.

**Cylinder Speed:-** 240-260 RPM

**Weight:-** Nett 160 kgs., gross 180 kgs.

**Floor Space:-** Space occupied: 1' 6" x 2' 6"  
 Working space required: 2' 6" x 5' 0"

**Attendance:-** One operator can handle 6-12 machines.

**Production:-** Based on 10 working hours:  
 3" Cylinder diam. machine: 5-8 doz. pairs of socks.  
 3½" " " " : 4-5 doz. pairs of socks.  
 3¾" " " " : 2-4 doz. pairs of socks.

**Advantages:-** Automatically knits welt, simple operation, low power consumption, high production capacity, smooth and first class products possible.

Handles mercerized cotton yarn, cotton threads etc.


Welt can be knitted with any desired elasticity, sole size and heel height can be adjusted by the chain.

Stop motion in case of needle breakage by signal bell.

*N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.*

CODE: RT - 2010

## 皮式電力織襪機 AUTOMATIC HOSIERY KNITTING MACHINE MODEL B



中國運輸機械進口公司經售  
 Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
 香港代理處：華潤公司  
 Hong Kong Agency: CHINA RESOURCES CO.  
 BANK OF CHINA BUILDING  
 HONG KONG  
 CABLE ADDRESS: "CIRECO."

This machine is specially manufactured for knitting socks after the rib top is completed. It is to be fixed on the cylinder provided with equal number of needles to complete knitting of the rib top sock.

**Specification:-** Available in different cylinder diameters with number of needles as follows:-  
 3" Cylinder diam. 96, 120, 140 needles for 6s and 20s counts yarn.  
 3½" Cylinder diam. 160, 176, 188, 200 needles for 32s/2 and 42s/2 counts thread.  
 3¾" Cylinder diam. 200, 220, 260, 280 needles for 60s/2 and 84s/2 counts thread.

**Power Required:-** ½ HP for single machine, 5 HP for 12 machines in case of group drive.

**Cylinder Speed:-** 260-285 RPM.

**Weight:-** Nett 150 kgs., gross 170 kgs.

**Floor Space:-** Space occupied ... .. 1'-6" x 2'-6"  
 Working space required ... .. 2'-6" x 5'-0"

**Attendance:-** One operator can handle 2-3 machines

**Production:-** Based on 10 working hours.  
 3" Cylinder diameter machine: 7-9 doz. pairs  
 3½" " " " : 7-8 " "  
 3¾" " " " : 5-6½ " "

**Advantages:-** Low power consumption, high production capacity.

Handles mercerized cotton yarn, cotton threads, etc.

Welt can be knitted with any desired elasticity, sole size and heel height can be adjusted by the chain.


Stop motion in case of needle breakage by signal bell.

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT-5001

四開鉛印機 (又名六度印刷機)

CYLINDER JOB PRESS,  
 WITH FLYER DELIVERY  
 MODE CJQ



中國運輸機械進口公司經售

Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION

香港代理處：華潤公司

Hong Kong Agency: CHINA RESOURCES CO.

BANK OF CHINA BUILDING  
 HONG KONG  
 CABLE ADDRESS: "CIRECO."

Model CJQ is a stop-cylinder letter-press for ordinary job work. Constructional features include: carriage drive by rod motion with 2 roller tracks; cylinder inking unit with 3 inking rollers; ink box with duct blade. Delivery cylinder is of the clear off type and the rotation of the impression cylinder is stopped by a handle.


Paper is fed by hand and delivered to the pile board by flyer system. The press is arranged for motor drive but at the same time it can be driven by foot treadle.

Models:	CJQ
Sheet Size:	457 x 610 mm (18" x 24")
Type Bed:	483 x 635 mm (19" x 25")
Chase, inside measurement:	445 x 597 mm (17 3/4" x 23 3/4")
Type Matter Locked in Chase:	457 x 610 mm (18" x 24")
Impressions per Hour:	1500
Flywheel Revolutions per Impression:	
Installation Floor Space:	1800 x 1250 (72" x 50")
Pulley Diameter x Width:	300 x 50 mm (12" x 2")
Weight:	Net: 1100 kgs. approx. Gross: 1500 kgs. approx.
Shipping Space:	3 cubic meters approx

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT - 5002

## 對開切紙機 PAPER CUTTING MACHINE, MODEL PC - 36



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."




This machine is so arranged that it can be driven either by hand or by power. It is of sturdy construction and has a high production capacity. The knife is automatically disengaged at its highest position. The knife holder is provided with double side connecting rods for diagonal cutting. The height of the table can be adjusted to avoid under or over cutting. The back gauge is adjusted by means of spindle and crank. The pressing beam is operated by a hand wheel. For power drive, an electric motor of 1½ H. P. is required. Starting and stopping of the machine are effected by a coupling clutch operated by a hand lever. This model is constructed for small enterprise, but can be utilized as a good auxiliary machine in large printing establishments.

Model:	PC-36
Length of Cut:	915 mm (36")
Height of Stack:	130 mm (5-1/8")
Table Surface:	1070 x 915 mm (42 1/2" x 36 1/2")
Installation Floor Space:	2060 x 2400 mm (82" x 96")
Weight:	Net: 1100 kg. approx. Gross: 1400 kg. approx.
Shipping Space:	2.5 cu. m. approx.

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT-9003

# 全張磨鋅皮機 ZINC PLATE GRAINING MACHINE, MODEL GM



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
HONG KONG Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."


THIS MACHINE is for cleaning and graining zinc plates for offset works.  
Glass, ceramic or steel marbles with sand are used, which may be supplied, if required.  
It is directly driven by motor through vee belting.

Model:	GM
Inside Measurement of Box:	1730 x 1270 mm (68" x 50")
Speed:	120 rpm
Installation Floor Space	2000 x 1450 mm (80" x 58")
Motor:	1½ H. P.
Net Weight:	1150 kgs. approx.
Gross Weight:	1400 kgs. approx.
Shipping Space:	3.6 cu. m. approx.

*N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.*

CODE: RT-5004

全張自動切紙機  
AUTOMATIC PAPER CUTTING MACHINE,  
MODEL PC-50



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

This machine is especially suitable for large factories desirous of having a modern machine of high output. Clamping of the material, cutting and raising of the knife take place automatically. The automatic clamping device acts immediately after the machine has been started; it transmits pressure upon the full depth of the pile. Mechanical forward and backward movement of the back gauge are controlled by a lever. The exact distance between the knife and the back gauge is indicated by a cutting space indicator which, in conjunction with the side gauge on the front table, facilitates feeding and ensures perfect square cut. The main shaft is equipped with a multi-disc clutch, by means of which the cutting pressure can be regulated. The machine is driven by an electric motor, all driving belts being effectively guarded.


Model:	PC-50
Length of Cut:	1270 mm (50")
Height of Cut:	130 mm (5-1/8")
Time per Cut:	4 seconds
Installation Floor Space:	2450 x 2600 mm (98" x 104")
Motor:	5 H. P.
Weight:	Net: 3600 kgs. approx. Gross: 4300 kgs. approx.
Shipping Space:	11 cu. m. approx.

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT-5005

### 三面切紙機

### THREE KNIFE BOOK TRIMMING MACHINE, MODEL BT



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

This machine is very popular to book-binding factories. It simultaneously trims stacks of paper, books, etc. on three sides. The automatic clamping device acts before the cutting operation; it transmits pressure on the entire top surface of the pile. The adjustment of the side-knives and of the back gauge, which becomes necessary for trimming a pile of another size, can be made in the most simple manner. Form plates of different sizes can be supplied at buyers' option.


The cutting zone is protected with guard screen so that the machine is accident proof.

Model:	BT
Number of Cutting Knives:	3
Time of each Cutting:	10 seconds
Minimum Size to be Cut:	51 x 78 mm (2" x 3-1/8")
Maximum Size to be Cut:	254 x 406 mm (10" x 16")
Height of Stack:	57-132 mm (2 1/4"-5 1/4")
Installation Floor Space:	2200 x 2100 mm (88" x 84")
Motor:	3 H. P.
Weight:	Net: 3600 kg. approx. Gross: 3800 kg. approx.
Shipping Space:	9.2 cu. m.

*N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.*

CODE: RT - 5006

## 電 動 訂 書 機 WIRE STITCHING MACHINE, MODEL WSP



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

This machine is specially made for book binding work. It is driven either by electric motor or by treadle. For book binding, round shaped wire is used, the staple is struck from underneath and is bent forward.


Model:	WSP
Thickness:	15 mm (5/8")
Staple Length:	12.7 mm (1/2")
Maximum Capacity:	120 staples per minute
Installation Floor Space:	686 x 711 mm (27" x 28")
Motor:	1 H. P.
Weight:	Net: 160 kg. approx. Gross: 230 kg. approx.
Shipping Space:	1 cu. m. approx.

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT-5007

# 拖 紙 機

## LIFTING TRUCK MODEL LT



中國運輸機械進口公司經售  
 Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
 香港代理處：華潤公司  
 Hong Kong Agency: CHINA RESOURCES CO.  
 BANK OF CHINA BUILDING  
 HONG KONG  
 CABLE ADDRESS: "CIRECO."


One of the important operations in any printing establishments is to handle materials efficiently. This hand lifting truck facilitates material handling, thereby reducing production cost.

Model:	LT
Maximum Load:	750 kg.
Lifting Height:	660 mm (26")
Size:	960 x 470 x 160 mm (38" x 18½" x 6½")
Weight:	Net: 118 kg. approx. Gross: 140 kg. approx.
Shipping Space:	0.256 cu. m. approx.

*N.B.—For improvement of this machine, we reserve the right to alter either the design or the specification.*

CODE: RT-5006

500 噸液力壓紙版機  
HYDRAULIC MATRIX MOULDING PRESS  
500 TONS CAPACITY




中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

CODE: RT - 5009

Speed of Matrix Moulding:	20 sec. per matrix
Maximum Pressure:	500 tons
Effective Pressure for Moulding Newspaper Matrix:	260 - 320 tons
Maximum Size of Matrix:	540 x 700 mm
Maximum Width of Working Table:	720 mm.
Power Required:	1½ H. P.
Overall Dimension:	Length 1.64 x width 1 x height 1.6 meter
Net Weight:	3,800 kg. approx.
Gross Weight:	4,050 kg. approx.
Shipping Space:	2.66 cu. meter approx.

全張雙迴轉印刷機  
TWO REVOLUTION MACHINE  
MODEL 51 (FULL SIZE)



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."


N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

Speed of Matrix Moulding:	20 sec. per matrix
Maximum Pressure:	500 tons
Effective Pressure for Moulding Newspaper Matrix:	260 - 320 tons
Maximum Size of Matrix:	540 x 700 mm
Maximum Width of Working Table:	720 mm.
Power Required:	1½ H. P.
Overall Dimension:	Length 1.64 x width 1 x height 1.6 meter
Net Weight:	3,800 kg. approx.
Gross Weight:	4,050 kg. approx.
Shipping Space:	2.66 cu. meter approx.

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT - 5009

全張雙迴轉印刷機  
TWO REVOLUTION MACHINE  
MODEL 51 (FULL SIZE)



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."



I. Specifications:-

Press Table Dimension ... ..	1274 x 981 mm
Size of Roller (diameter x length) ... ..	∅ 533.4 x 1168 mm
Roller Rail (Height) ... ..	23.44 mm
Size of Ink Duct (Width x length) ... ..	1150 x 905 mm
Maximum Size of Sheet ... ..	1100 x 800 mm

2. Mechanical Features:-

Type ... ..	Single Printing Roller with increasing pressure
Impressing Pressure ... ..	5 Kg/cm <sup>2</sup>
Speed of Printing Roller ... ..	36-62 rpm.
Impressions per minute ... ..	18-31
Track of Distribution Rollers ... ..	(1) 40 mm (2) 38 mm

Power: A. C. motor, 3 phasa, 50 cycle, 220/380 volts, 5.5 KW, 1450 rpm.


Dimensions: 4200 x 2700 x 1700 mm

Weight: approx. 9800 kg.

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT-5010

鑄 字 機  
TYPE CASTING MACHINE,  
MODEL TCL



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION

香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."


This machine is developed for high speed casting of sharp and clean types. The essential parts are made of high grade carbon steel, those which are subject to wear as well as the shafts are hardened and heat treated. The most important part of this machine, the matrix case, is made of special chromium alloy steel and precision ground ensuring production of sharp metal types. It is arranged for heating by electric current, consuming about 3 KW. The machine is equipped with a  $\frac{3}{4}$  H. P. electric motor and a type casting case, the size of which is at buyer's option.

Model:	TCL
Casting Range:	6 points to 28 points
Production per Minute:	For 6 points, 130-150 castings
Installation Floor Space:	850 x 650 mm (34" x 26")
Weight:	Net: 420 kg. approx. Gross: 485 kg. approx.
Shipping Space:	1.1 cu. m. approx.

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT-5011

鑄 字 盒  
TYPE-CASTING CASE,  
MODEL TCC



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

These Casting Cases are made of special chromium alloy steel, precision ground and heat treated ensuring production of clear and sharp metal types. They are available in three models:

- TCC-A: Fixed model used for casting assigned sizes of types.
- TCC-B: Adjustable model used for casting various sizes of types of uniform height.
- TCC-C: Universal quotation casting box for casting hollow types from No. 2 to No. 6.


Each type-casting case is provided with 3 sets of steel moulds, specification of which is at buyer's option.

Dimension: 230×180×90 mm (9"×7"×3½")  
Weight: 4 kgs. approx.

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT-5012

# 熔鉛爐連泵浦 MELTING OVEN WITH PUMP, MODEL RN-14



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION

香港代理處：華潤公司  
HONG KONG Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

This oven is characterised by its simplicity and efficiency. It can be installed at any place to cast stereo-plates for Model RP 1-64 and RP 4-64 large size Rotary Presses. Metal is pumped through a charge pipe and forced into the casting box by pushing its hand-lever. A single stroke of the lever will deliver a quantity of metal sufficient to form one plate.

Specifications:

Capacity of Pot:	2,600 kg. of lead alloy
Displacement of Pump:	8,600 cm <sup>3</sup>
Surface of Oven Grate:	3,726 cm <sup>2</sup>
Fuel Used:	Bituminous Coal
Net Weight:	2,500 kg. approx.
Gross weight:	2,800 kg. approx.
Shipping Space:	5.5 cu. meter approx.

Attached Equipments:


1 pc.	Thermo-couple Pyrometer
1 set	Chimney 7 m x 200 mm $\phi$

*N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.*

CODE: RT-5013

方 箱 印 刷 機

PLATEN PRESS, MODEL PP-14



中國運輸機械進口公司經售  
 Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
 香港代理處：華潤公司  
 Hong Kong Agency: CHINA RESOURCES CO.  
 BANK OF CHINA BUILDING  
 HONG KONG  
 CABLE ADDRESS: "CIKECO."


This is a fine art platen press suitable for general job printing and also for half-tone and zinc block works. It is built with sturdy bed and frame, a single disc and self-inking apparatus, friction clutch and brake. It is capable of a wide range of printing, requiring minimum power and space.

Model:	PP - 14
Chase, inside measurement:	330 x 432 mm (13" x 17")
Size of Platen:	355 x 508 mm (14" x 20")
Impressions per Hour:	1260
Installation Floor Space:	1270 x 1880 mm (50½" x 74")
Motor:	1 H. P.
Weight:	Net: 1,200 kg. approx. Gross: 1,500 kg. approx.
Shipping Space:	3 cu. m. approx.

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT - 5014

元 盤 印 刷 機  
PLATEN PRESS, MODEL PP - 10  
FOR TREADLE DRIVE.



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

This model has a strongly built vertical bed, a single disc and self-inking apparatus for Perfect inking distribution. It is equipped with a device for regulating and throwing off impressions in any position of the platen.

Model:	PP-10
Chase, inside measurement:	254 x 381 mm (10" x 15")
Size of Platen:	279 x 406 mm (11" x 16")
Impressions per Hour:	1200 to 1800
Installation Floor Space:	1422 x 1219 mm (56" x 48")
Weight:	Net: 530 kg. approx. Gross: 650 kg. approx.
Shipping Space:	1.7 cu. m. approx.


N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT-3015

# 單捲筒十六版輪轉印報機

## UNI-REEL 16-PAGE NEWSPAPER ROTARY PRESS

MODEL RPI-64



中國運輸機械進口公司經售

香港代理處：華潤公司

Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CINTECO."

This rotary press is capable of printing newspaper with a daily circulation from 50,000 to 100,000 copies. The construction has been carefully designed with due consideration of the large dimension of the cylinder of 4-plate width. It is both easy to install and to dismantle. Every part is so designed as to simplify the operation.

This Rotary Press is composed of two printing units and a second colour unit which is fixed on the top. The oil ring lubricated bearings of the cylinder are completely enclosed and fitted with an eccentric mechanism for adjusting the center of the shaft to ensure printing accuracy and correct pressure. Its main drive comprises of a 35 h. p. A. C. commutator motor with push button control for speed regulation. To stop the rotary press, an electromagnetic brake is provided.

This Rotary Press is equipped with a tapeless double folder and one of 45° turning bars.

This press handles paper reels of 64" width, but those of 63" are also adaptable

For feeding the paper there is a 5 H. P. motor but a hand feeding lever is also provided.

#### Technical Data:

Maximum Printing Surface	14 $\frac{1}{2}$ " x 21"
Size of 4-page paper (with 64" width reel)	22" x 32"
Printing Diameter	14"
Number of Plates	16 pcs.
Number of Plates for Second Colour	8 pcs.
Thickness of Plates	14 mm.
Thickness of Blanket	5 mm.
Standard Speed	12,500 cyl r/h
Maximum Speed	13,000 cyl r/h

#### Output:

No. of Sheets per copy	No. of Pages	Copies/Hour	No. of Pages with Colour	Width of Reel
$\frac{1}{2}$	2	100,000	1	64"
1	4	50,000	2	64"
$1\frac{1}{2}$	6	25,000	3	64"
2	8	25,000	4	64"
$1\frac{1}{2}$ double	12	12,500	6	64"
4	16	12,500	8	64"

Power Required	35 H. P.
Overall Dimension	length 5.3 m. width 4.5 m. height 2.65 m.
Net Weight (including electrical equipment)	29,500 kg. approx.
Gross Weight (including electrical equipment)	32,500 kg. approx.
Shipping Space	46.5 cu. m. approx.

#### Standard Equipment:


- 1-Stereo-plate Casting Machine Model RD-14
- 1-Automatic Boring Machine (Autoshaver) Model RF-14
- 1-Melting Oven with Pump Model RN-14
- 1-Hydraulic Matrix Moulding Pump 500 Tons Capacity, Model PH-2

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

right to alter either the design or the specification.

CODE: RT-5016

## 單捲筒八版輪轉印報機 UNI-REEL 8-PAGE NEWSPAPER ROTARY PRESS MODEL PR 1-32



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
HONG KONG Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

This Rotary Press is designed for printing 10,000 to 50,000 copies of newspapers daily. It is also adaptable to book and job printings. Rigidity in construction and simplicity in operation are its essential features. Its main frame is of the arch type which provides ample working space, and its parts are arranged within convenient reaches of the worker.

This press is composed of 2 printing units and a second colour unit which is fixed on the top. The oil ring lubricated bearings of the cylinder are completely enclosed. An eccentric mechanism is provided for adjusting the center of the shaft to ensure printing accuracy and correct pressure. The length of the cylinder is equal to the width of two plates.

The press is complete with one tapeless folder. Each complete issue of the newspaper will be automatically folded into two platts by means of the folding triangles and cylinders and sent out of the rotary press in consecutive order through its tape delivery. A counter with recording marks for every 25 copies or 50 copies of newspapers delivered, is attached to the press for purpose of computation.

The press takes a single paper reel of 32" width, but reels from 31" up to 34" are also adaptable. Lifting device for paper reel is provided to save work and time. Another convenient feature is that two such presses can be connected together to convert into a two-reel 16 page press.

The electric drive consists of a variable speed A. C. commutator motor with remote control of speed by push buttons.

In case of emergency an electro-magnetic brake automatically stops the machine.

#### Technical Data:

Maximum Printing Surface	...	...	...	14 $\frac{3}{4}$ " x 21"
Size of 4-page Copy (with 32" width reel)	...	...	...	22" x 32"
Standard Width of Paper Reel	...	...	...	32"
Printing Diameter	...	...	...	14"
Number of Plates	...	...	...	8 pcs.
Number of Plates for Second Colour	...	...	...	4 pcs.
Thickness of Plates	...	...	...	14 mm.
Thickness of Blanket	...	...	...	5 mm.
Standard Speed	...	...	...	12,500 cyl r/h

Output: Average as follows:

No. of Sheets per copy	No. of Page	Copies/Hour	No. of Pages with Colour	Width of Reel
1	2	50,000	1	32"
1	4	25,000	2	32"
2	8	12,500	4	32"

Power Required ... .. 20 H. P.  
Overall Dimension ... .. length 5 x width 3.5 x height 2 meters

Standard Equipment includes one each of:


1-Matrix Moulding Press	1-Router with Electric Drive
1-Oscillating Cup Casting Plant	1-Shaver for Curved Stereos
1-Melting Pot	1-Trimming Apparatus
Total Weight (including stereotyping set and electric equipment):	12,650 kg. (approx.)
Gross Weight	12,250 kg. approx.
Shipping Space	22.65 cu. m. approx.

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT-5017

## 三色凸版機

### PLATEN PRESS MODEL PP-16



#### 中國運輸機械進口公司經售

Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION

香港代理處：華潤公司

Hong Kong Agency: CHINA RESOURCES CO.

BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO,"




In introducing this platen press we provide a machine which produces finest tint work as well as ordinary job work at highest speed. Bed and frame are cast in one piece. The machine is furnished with two tension rods, cylindrical inking with four inking rollers, friction clutch and brake. Operation of this machine requires minimum power and space.

Model:	PP16
Chase, inside measurement:	394 x 560 mm (15½" x 22")
Size of Platen:	420 x 585 mm (16½" x 23")
Impressions per Hour:	1500
Installation Floor Space:	2032 x 1321 mm (80" x 52")
Pulley, diameter x width:	330 x 75 mm (13" x 3")
Motor:	2 H. P.
Weight:	Net: 1500 kg. approx. • Gross: 2000 kg. approx.
Shipping Space:	3.8 cu. m. approx.

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT - 5018

對開膠版打樣機  
SINGLE COLOUR OFFSET MACHINE  
MODEL OHF WITH FLYER DELIVERY  
MODEL OHC WITH CHAIN GRIPPER DELIVERY



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO,"


This is a popular machine for any offset printing establishment, capable of handling intricate colour printing on any kind of paper. It is provided with either flyer delivery or chain gripper delivery at buyers' option. Other unique features of this machine are: improved inking device, dense and sharp impression and perfect register.

Model:	OHF & OHC
Printing Surface:	610 x 915 mm (24" x 36")
Plate Size:	725 x 915 mm (28½" x 36")
Paper Size:	610 x 915 mm (24" x 36")
Blanket Size:	864 x 915 mm (34" x 36")
Production:	2700 sheets per hour on one side.
Drive Ratio:	5:1
Pulley Size:	550 mm (22") diameter
Motor:	3 h. p.
Installation Floor Space:	3000 x 2000 mm (10' 0" x 6' 8")
Weight:	Net: 3500 kg. approx. Gross: 4360 kg. approx.
Shipping Space:	12 cubic meters approx.

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT-5019

## 澆 鉛 版 機 STEREO-PLATE CASTING MACHINE MODEL RD-14



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO,"

This machine is designed for mechanical casting of curved stereo-plates for rotary presses. It is oftenly used in combination with Model RN-14 melting oven. Left or right hand operated types can be supplied as required.

The installation of this machine is simple as only a concrete foundation is required for the work.

It comprises of a turnable vertical cylinder in the center of a curved casting box. After the machine is set in motion by a lever movement, molten metal is pumped into the mould and a stereo-plate is formed. Thereafter, the stereo-plate travels with the cylinder and is trimmed. Water cooling system is provided throughout the entire casting process.


Specifications:

Dimension of Stereo-plate:	To customers' requirement
Capacity:	1 plate per minute
Power required:	$7\frac{1}{2}$ H. P.
Space Required for Machine (including Oven & Pump) in sets:	Length 2xwidth $2\frac{1}{2}$ xheight 2 meter
Net Weight:	2,000 kg. approx.
Gross Weight:	2,200 kg. approx.
Shipping Space:	4.8 cu. meter approx.

*N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.*

CODE: RT-6001

捲 烟 機  
HIGH SPEED CIGARETTE - MAKING MACHINE



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

## Specification:

Production per minute ... 1000 pcs. (About 80 to 90 kgs.  
of tobacco are required to produce 50,000 cigarettes)

Length of Cigarette ... 70 mm

Power Required ... 3 H. P. Motor 1450 rpm.

Floor Space (L x W x H) ... 10 ft. x 6 ft x 7 ft.

Packing ... In two wooden cases.

a) Measurement of Case #1 ...  $10\frac{1}{2} \times 3\frac{1}{2} \times 5$  ft.

b) Measurement of Case #2 ...  $6\frac{1}{2} \times 5 \times 7\frac{1}{2}$  ft.

Weight ... Net: 2500 kg.  
Gross: 3100 kgs.

## Auxiliary Machines

1. Tobacco Cutting Machine with 10" knife: Capacity—140 kgs./hour
2. Tobacco Cutting Machine with 16" knife: Capacity—450 kgs./hour
3. Stem Crushing Machine: Capacity—200 kgs./hour
4. Cigarette Carton Making Machine
5. Waxed Paper Wrapping Machine
6. Packing Machine
7. Knife Grinding Machine
8. Tobacco Drying and Cooling Machine
9. Unpacking Machine
10. Tobacco Leaves Steaming Machine
11. Tobacco Leaves Baking Machine
12. Flavour Mixing Machine

N.B.—For improvement of the machine, we reserve the  
right to alter either the design or the specification.

CODE: RT-6002

## 製餅干機設備

## BISCUIT BAKERY EQUIPMENT

中國運輸機械進口公司經售


Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION

香港代理處：華潤公司


Hong Kong Agency: CHINA RESOURCES CO.

BANK OF CHINA BUILDING  
HONG KONG


CABLE ADDRESS: "CIRECO."



BISCUIT DOUGH MIXER  
MEDIUM SIZE



BISCUIT MEAL-SHEETER  
MEDIUM SIZE



BISCUIT MOLDING PRESS  
MEDIUM SIZE

## Specification:

1. Biscuit Molding Press (Medium size) 製餅軋機(中型)
  - a) Adjustable Thickness of Meal Sheets 3-19 mm
  - b) Adjustable Speed of Molding 15-130 times per minute.
  - c) Output Capacity per hour ... Maximum 370 kgs.  
Minimum 120 kgs.
  - d) Power Required ... 7½ H. P. Motor
2. Biscuit - Dough - Mixer (Medium Capacity) 拌粉機(中型)
  - a) Dimension... Length 1700 mm  
Width 899 mm  
Depth 1700 mm
  - b) Flour Treated per Batch ... 150 kgs.
  - c) Power required ... 3 H P Motor
3. Biscuit Meal-Sheetter (Medium Size) 皮子機(中型)
  - a) Dimension of Table ... Length 2700 mm  
Width 800 mm  
Height 840 mm
  - b) Attached Equipment:
 

Rubber Belting 76 x 3556 mm...	2 pcs.
Motor Belt Pulley ...	1 pcs.
Foundation Bolts ...	4 pcs.
  - c) Power Required ... 5 HP Motor.
4. Circulated Turbo-Fan Oven 烘爐
  - a) Type ... 10 trays, 5 shelves, 2 layers in concentric
 


Oven Conveyor:	Outer Diameter	3150 mm
	Height	3300 mm
	Length of Conveyor Axis	4970 mm
  - b) Size of Fire-Brick Oven Shell ...
 

	Length	4700 mm
	Width	4700 mm
	Height	7000 mm
  - c) Power Required ... 2 HP Motor.

N.D.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT-8001

## 製大頭針機 PIN MAKING MACHINE



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
HONG KONG Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."


Specification:

Revolution: ...	300 R. P. M.
Raw Materials Required ...	Iron Wire, BWG 22.
Production ...	14 cm per 8 hours
Measurement ...	Length 52 inches
	Width 48 inches
	Height 52 inches
Weight ...	625 kgs.
Motor Required ...	1½ - 2 H. P.

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT - 8002A

自動壓杯機  
AUTOMATIC MOULD  
FOR MAKING DRINKING GLASS.



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."


Driven by electric motor. Compressed air of 40-45 lbs./sq. in. pressure is used.  
Suitable for making drinking glass. Machine revolves at 11-19 revolutions per minute.

Production: 900 doz. per 8 hour-day  
Overall Dimensions: 240 x 135 x 110 cm.  
Weight: 1850 kgs.  
Power Required: 1.2 kw.

*N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.*

CODE: RT-8002B

半自動壓杯機  
SEMI-AUTOMATIC MOULD  
FOR MAKING DRINKING GLASS.



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."




Suitable for making drinking glass, dish, etc. with maximum height of 8 inches and diameter of 6 inches. Compressed air of about 45 lbs./sq. in. pressure is used.

Production: 450 doz. per 8 hour-day  
Overall Dimension: 96½" x 52" x 32"  
Weight: 1,650 kgs.

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT-8002C

三鐵碗吹瓶機  
BOTTLE BLOWING MACHINE  
WITH 3 MOULDS.



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."


Usage: Capable of blowing glass bottles  
of 50 to 500 cu. cm. contents.  
Capacity: About 6,000 pcs. per 8 hour-day  
Overall Dimension: 29" x 29" x 65"  
Weight: 850 kgs.

Compressed air of 25 to 30 lbs. per sq. in. pressure is to be used for blowing the glass bottles.


N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT-8603

擱 鈕 機  
STUD MAKING MACHINES  
雙行程擱鈕雄片落料翻邊車  
PUNCH PRESS (FOR MALE PART OF STUD)  
ITEM No. A-1




雙行程擱鈕雄片捲邊車  
PRESS (FOR MALE PART OF STUD)  
ITEM No. A-2





中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

單行程撥鈕雌片沖條車  
PRESS (FOR FEMALE PART OF STUD)  
ITEM No. B-1





三行程撥鈕雌片落料翻邊車  
PUNCH PRESS (FOR FEMALE PART OF STUD)  
ITEM No. B-2



手扳裝撥鈕彈簧捲邊車  
HAND DRIVEN PRESS (FOR FEMALE PART  
OF STUD) ITEM No. B-3

撥鈕銅絲彈簧車  
WIRE SPRING MAKING MACHINE  
ITEM No. C.



撥鈕車沖模  
DIES.

## Specifications:

Name of machine	Spindle speed rpm	Stroke m/m	H. P. required	R. P. M.	Overall dimension m/m	Weight Kg.	Output per min.
(A) 1	150	29 x 39	2½	960	1220 x 1070 x 2160	1725	750 pcs.
(A) 2	140	39 x 39	1/2	960	530 x 310 x 770	130	280 pcs.
(B) 1	150	29	2½	960	1220 x 1070 x 2160	1700	750 pcs.
(B) 2	150	10 x 30	2	960	990 x 690 x 1710	1400	750 pcs.
(B) 3					390 x 210 x 410	17	18 pcs.
(C)	150		1/2	960	950 x 690 x 970	130	600 pcs.
(D)	500		7½			250	

All power driven machines are coupled to the motor by Vee belt.

The name of machine is listed and explained as follow:

## NAME OF MACHINE

## (A) For Male part of Stud

1. Punch Press for cutting copper or zinc alloy strips into pieces and at the same time bead and sewing holes are formed and edge is turned downward.
2. Press for folding the edge of the stud.

## (B) For female part of Stud

1. Press for making bead and sewing holes on strips,
2. Punch Press for cutting strips into pieces and at the same time edge is turned upward.
3. Hand driven Press for folding the edge of the Stud and at the same time wire spring is inserted.


## (C) Wire Spring Making Machine

- (D) Vertical Air Compressor for the supply of compressed air to each machine to blast scraps from the dies.

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT-8004 A

## 製木螺絲全套設備 WOOD SCREW MAKING MACHINERY



(A) WIRE DRAWING MACHINE (ARRANGED IN SERIES)

## Specifications:

Diameter of Drawing drum in inches	Number of rel. / min.	Distance between spindles in inches	Thickness of wire to be drawn (B.W.G.)	Weight of Machine in lbs.	Output in 8 hours in lbs.	Power consumption in H.P.
24	25	55	8/0 - 1	3800	6600	12
23	30	51	4/0 - 4	3650	4400	10
22	45	47	1 - 8	3450	3520	8
21	55	47	4 - 11	3350	2640	6

中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION

香港代理處：華潤公司  
HONG KONG Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

**(B) SINGLE STROKE OPEN DIE COLD HEADER (UNIVERSAL TYPE)****Specifications:**

Size...	1/8"	1/4"	3/8"
	H-1	H-2	-3
Capacities:			
Max. dia. of wire S.G.) ...	0-5	4-10	9-14
Max. length shank ...	1"	2"	3"
Min. length wire blank ...	3/8"	1"	1 1/2"
Max. length wire blank ...	1 1/4"	2-3/8"	3 3/8"
Output per min. (pieces) ...	225/250	125/150	100
Output in 8 hours (gross) ...	480/550	300/400	245
Flywheel:			
Approximate weight ...	150	400	820
Diameter and face ...	ø24" x 4"	ø42" x 5 1/2"	ø48" x 8"
Motor:			
H. P. ...	2	5	7 1/2
R. P. M. ...	960	1400	1400
Floor Space ...	2'2" x 3'9"	3'10" x 5'10"	4'5" x 7'9"
Net Weight (lbs.) ...	2500	3750	8900
Boxed Weight (lbs) ...	2800	4350	9200
Boxed dimension ...	45 cu. ft.	120 cu. ft.	190 cu. ft.

**(C) HEAD TURNING & SLOTTING MACHINE  
(TWO SPINDLE MACHINE)**

The bolt head is first turned off then slotted, then again finish turned.


**Specifications:**

Size ...	S - 0	S - 1
Capacities:		
Max. dia. (S.G.) Wood Screw Gauge ...	0 - 8	7-14
Max. Length of Wood Screw ...	2"	3 1/4"
Output per min. (pcs.) ...	22-24	18-20
Output in 8 hours (gross) ...	60-70	50-55
Motor:		
H. P. ...	0.75	1
R. P. M. ...	1400*	1400
Floor Space ...	2' x 3'	2'6" x 3'6"
Net Weight (lbs) ...	650	800
Boxed Weight (lbs) ...	800	970
Boxed dimension ...	40 cu. ft.	46 cu. ft.

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT - 8004 B

製木螺絲全套設備  
WOOD SCREW MAKING MACHINERY  
木螺絲車  
(D) SCREW THREADING MACHINE



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
HONG KONG Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

## Specifications:

Size	T-0	T-1	T-2
Capacities:			
Max. dia. (S.G.) wood screw gauge	0-8	7-12	10-16
Max. length of wood screw	$\frac{1}{4}$ " - $1\frac{3}{4}$ "	$\frac{3}{8}$ " - $2\frac{1}{2}$ "	$\frac{1}{2}$ " - $3\frac{1}{2}$ "
Output per min. (pcs.)	10-18	6-16	4-10
Output in 8 hours (gross)	25-50	18-40	13-25
Floor Space	2' x 3'	2'6" x 3'6"	2'6" x 4'0"
Motor:			
H. P.	0.5	0.75	1
R. P. M.	1400	1400	1400
Net Weight (lbs.)	650	800	1000
Boxed weight (lbs.)	800	970	1170
Boxed Dimension	40 cu. ft.	46 cu. ft.	52 cu. ft.

## (E) AUXILIARY MACHINE &amp; APPARATUS

## 1. Scouring and Cleaning Drums (Rumblers)

Length	34"
Diameter	22"
Motor: H. P.	1
R. P. M.	960
Net Weight	1000
Boxed Weight	1320
Boxed Dimension	14 cu. ft.

Rumblers with sheet iron cases and those with wood cases are required, the former for scouring the pressed blanks and the latter for cleaning the half finished and the finished wood screws coming from the head turning and slotting machines and the screw threading machines respectively.

## 2. Milling Cutter Grinding Machine (Automatic Type)

This Machine automatically sharpens the teeth of milling cutter for the head turning and slotting machines, where they have become blunt.

## 3. Wire Reel

For the heading presses wire reels are required for unwinding the wire.

## 4. Centrifugal pump directly coupled with motor.

The head turning and slotting machines as well as the screw threading machines requires a constant supply of a solution of soda for cooling the cutter and milling cutter.

\* \* \* \* \*

**Machines for an output of roughly 3000 gross of wood screw for 8 hours ranging in sizes from screw gauge No. 2 to S. G. No. 14 and 1/4" to 3" long are as follows:**

1 set	Wire Drawing Machines	W-1
3 sets	4 heads arranged in series	1/8"-H-1
3 sets	Single stroke open die cold header	1/4"-H-2
2 sets	Single stroke open die cold header	3/8"-H-3
50 sets	Screw threading Machines	T-0
24 sets	Screw threading Machines	T-1
24 sets	Screw threading Machines	T-2
44 sets	Head turning and slotting machines	S-0
36 sets	Head turning and slotting machines	S-1

N.B.—For in procurement of the machine, we reserve the right to alter either the design or the specification.


CODE: RT-8005

## 製安全別針全套設備


## SAFETY PIN MACHINES.

中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

WIRE STRAIGHTENING,  
CUTTING & SHARPENING  
MACHINE ITEM 1.




WIRE COILING MACHINE  
ITEM 2.



雙行程冲頭車  
LOCK MAKING PRESS  
ITEM 3.



捲邊車  
LOCK GRIPPING PRESS  
ITEM 4.



**Item 1** Wire Straightening, Cutting & Sharpening Machine.

By means of this machine, low carbon steel wire in the form of coils is straightened, next cut into blanks of definite length (say 6.7 cm), and then one end of the blank is ground to form a sharpened point.

Motor required:  $\frac{1}{2}$  HP, 960 RPM

Overall Dimension: 1630 x 1150 x 1450 mm

Weight: 800 kg.

Output: 120 pieces per minute

**Item 2** Wire Coiling Machine

The blank with one end sharpened is coiled or bent into the required form with a helix giving the effect of a spring.

Motor required:  $\frac{1}{2}$  HP, 960 RPM

Overall Dimensions: 870 x 840 x 1020 mm

Weight: 240 kg.

Output: 120 pieces per minute

**Item 3** Lock Making Press

The Press is of dual action type. In one action, raw material steel sheet is cut into small piece as blank for the other action, under which the blank is pressed to form Lock (but not in its final form).

Motor required:  $\frac{1}{2}$  HP, 960 RPM

Overall Dimension: 660 x 510 x 1600 mm

Weight: 310 kg.

Output: 144 pieces per minute

**Item 4** Lock Gripping Press

The coiled wire and the Lock after being assembled by hand is fed, manually, into this Press, in which the Lock is pressed into the final form.

Motor required:  $\frac{1}{2}$  HP, 960 RPM

Overall Dimensions: 980 x 950 x 1010 mm

Weight: 270 kg.

Output: 120 pieces per minute

**Remarks:**

The finished product is then electro-plated and the processes are:

- barreling, to cleanse the safety pins.
- copper-plating, preparatory to nickel plating.
- nickel plating.


Particulars for such equipment, as well as those of Punch & Dies for Punching Presses, will be supplied upon request.

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT. 8006

## 鋼筆刻名機

### ENGRAVING INSTRUMENT.

**使用說明**

- |         |  |         |                       |
|---------|--|---------|-----------------------|
| 1. 簽名紙  | 放入隔層玻璃內將鋼筆旋緊使玻璃不動即可                            | 6. 電珠   | 如遇陰天或夜晚光線不足時使用之       |
| 2. 執筆機鈕 | 在機壳外面用手指將它按下                                   | 7. 元寶羅絲 | 將它旋緊裝入刻字器即可拔出         |
| 3. 執筆器  | 將鋼筆橫插入使他平服即可                                   | 8. 換針机頭 | 磨鋒鋼筆頭旋下換入新針舊針保存磨尖仍可使用 |
| 4. 機鈕   | 左手握4右手拿5通斷割左手須放手過大中小鋼筆塑膠軟料將4往上運旋膠木硬料相反向下運旋隨意調節 | 9. 大羅絲  | 日久如遇鬆動則先將它旋緊          |
| 5. 指針   | 像寫字式與4配合起來慢慢地點字移動指針                            | 10. 橫羅絲 | 將它較緊些再將9旋緊            |

附言初刻時先用廢鋼筆使作試刻數次即會

中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION

香港代理處：華潤公司


Hong Kong Agency: CHINA RESOURCES CO.

BANK OF CHINA BUILDING  
HONG KONG

CABLE ADDRESS: "CIKECO."



# 銅筆刻名機 ENGRAVING INSTRUMENT.




## Working Instructions :-

1. Signature specimen Place specimen of signature underneath glass plate (1), and tighten screw.
2. Clamp button Press button (2).
3. Clamp Insert pen and have it held firm by clamp (3).
4. Impression control button Press (4) with left hand finger and hold (5) with right hand. Release left hand finger when encountering broken strokes. When engraving on pen of soft material, moving screw button upward; when engraving on pen of hard material, screw button downward. The impression is thus regulated.
5. Tracer Trace along the signature in concord with the impression control button.
6. Bulb This is intended to improve illumination whenever necessary.
7. Wing screw Loosen this screw to detach the eggshape engraver.
8. Chuck Screw off chuck to replace needle.
9. Big screw When big screw becomes loose after repeated use, loosen it first; tighten horizontal screw (10) and then tighten big screw.
10. Horizontal screw

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE : RT - 3005

# “飛人”牌18型鎖邊縫紉機 (供呢絨毛毯鎖邊用) OVERLOCK STITCH SEWING MACHINE “FLYING MAN” MODEL 18



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

Model 18 is a single thread overlock sewing machine for seaming, overedging or hemming work on all kinds of materials. It is specially adaptable for overedging woollen blankets.

The constructional features are compactness, easy threading, accessibility to moving parts and improved lubricating system. The pitch of the stitches can be adjusted from 2 to 6 mm by changing the cam.

The length of stitches can be adjusted up to 12 mm so that thick blankets can be seamed as desired. The sewing speed can be as high as 1200 stitches per minute enabling trained operators to overedge woollen blankets of normal size at a rate of 30 pieces per hour.

Length of stitch	12 mm.
Maximum sewing speed	1200 stitches per minute
Maximum pitch of stitches	6 mm.
Overall dimension (L x W x H)	300 x 136 x 255 mm.
Power required	$\frac{1}{2}$ HP.

#### Packing Information


Contents	Approximate Weight (kgs)		Approximate Measurement (cm)
	Nett	Gross	
1 set Head	12.5	20	

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT-3008

### “標準”牌81-6型工業用縫紉機

### THREE-THREADED OVERLOCK SEWING MACHINE “TYPICAL” MODEL 81-6



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIKECO."

This machine is fitted with auxiliary feed and trimmer and is specially made for sewing fabrics, hosiery or light materials. The machine produces elastic chain stitch and is also designed for TRIMMING, OVEREDGING and BLIND STITCH HEMMING or WELTING, these can be done in a single operation.

Apart from the foregoing, this machine has made possible, quality production, high speed and low operating costs to a degree greater than ever before. It is easy to handle, simple to adjust, sturdy in design, accurate in workmanship and is readily adapted to many kinds of work.

Length of stitch	3.6 mm.
Maximum sewing speed	3000 stitches per minute
Sewing width	1.5-5 mm.
Thickness of material sewn	5 mm.
Needles	System ( 81 x 1 )
Power required	$\frac{3}{4}$ HP.


#### Packing Information

Contents	Approximate Weight (kgs)		Approximate Measurement (cm)
	Nett	Gross	
1 set Head	18	27	52 x 36 x 40

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT - 4001

## 萬 能 帶 鋸 UNIVERSAL BAND SAW MACHINE



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO,"


Wheel diameter	800 mm
Speed of wheel	800 RPM
Max. sawing height...	570 mm
Max. sawing width...	715 mm
Max. width of sawing blade...	35 mm
Work table	940 x 790 mm
Max. inclination of table	40°
Electric Motor	
Power	4 - 5 KW
Speed	1500 RPM
Overall dimension	1809 x 943 x 2650 mm
Weight	920 kg. (approx)

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT-3001

“飛人”牌146-1型縫袋用縫紉機  
(用於縫麵粉袋食糖袋及其他谷物袋的封口)

BAG CLOSING MACHINE  
“FLYING MAN” MODEL 146-1



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

This model is designed for closing filled bags containing sugar, flour, grain or other products which are usually packed in bags.

The machine makes two-thread chain stitch, so that strong and elastic seams can be produced to tightly close the bags, thus preventing commodities from leaking out at the seams despite rough handling in transportation.

The machine is equipped with an adjustable conveyor, upon the moving belt of which the filled bags are placed. The bags are thus carried to the operator who guides them through the machine for stitching.

Bags measuring from 20 cm. to 85 cm. from the bottom of the bag to the line of stitching, can be handled on the machine, the conveyor being raised or lowered by turning two handles at the back of the machine to accommodate the various sizes of the bags. As the conveyor belt is 30 cm. wide, bags up to 40 cm. in thickness can be sewn.

The conveyor is capable of carrying three 100-pound bags at the same time or the equivalent weight in as many bags as can be accommodated on the conveyor belt.

The sewing machine head being mounted on a hinged frame can be raised or lowered by a hand wheel, thus slight variation in the height of the bags of the same capacity can be taken care of without adjusting the conveyor.

The machine is equipped with a shear which can be used to cut the thread after each bag is stitched. The shear is operated by a hand lever.

Length of stitch	12 mm.
Maximum sewing speed	1800 stitches per minute
Working space under arm	85 x 70 mm.
Overall dimension (L x W x H) of sewing head	300 x 360 x 260 mm.
Thickness of material sewn	8 mm.
Power required	1 HP.
Efficiency (approx.)	* 500 bags per working hour
Overall dimension of machine with conveyor (L x W x H)	1200 x 1200 x 2000 mm.

#### Packing Information


Contents	Approximate Weight (kgs)		Approximate Measurement (cm)
	Nett	Gross	
1 set Head	19	25	44 x 32 x 46
1 set Head & Conveyor	529	765	158 x 135 x 183

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT-3002

“飛人”牌124型縫袋用縫紉機  
(用於紙麻棉製袋的封口適用於水泥廠化工廠製袋廠用)

### GUNNY BAG CAP SEWING MACHINE “FLYING MAN” MODEL 124



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

This is the most powerful machine for making bags from burlaps and other heavy weight fabrics. It sews the bags either with single thread or two-thread chain stitch producing strong seams.

The machine is fitted with a positive drop feed and two separately hinged compensating presser feet, which ensure its successful operation on all grades of bag materials. This arrangement is particularly effective when hemming bags, as one of the presser feet rests upon the hem while the other rests on the body of the bag, each foot yielding independently according to the thickness of the work being sewn. A knee press for raising or lowering the presser feet is provided with each machine, enabling operator to use both hands in manipulating the work.

For convenience in threading the looper and to facilitate the making of adjustments, the front portion of the cloth plate is hinged so that it can be turned aside to permit easy access to the mechanism in the bed of the machine.

The machine is provided with an iron base which receives the dirt and surplus oil, thus helping to prevent the bags from becoming soiled while they are being sewn.

Length of stitch	12 mm.
Maximum sewing speed	1400 stitches per minute
Thickness of material sewn	15 mm.
Working space under arm	180 x 130 mm.
Overall dimension (L x W x H)	430 x 205 x 385 mm.
Power required	$\frac{1}{2}$ HP.


Packing Information

Contents	Approximate Weight (kgs)		Approximate Measurement (cm)
	Nett	Gross	
1 set Head	28½	40½	48 x 25½ x 43½

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT - 3009

“標準”牌69-41型工業用縫紉機  
LOCKSTITCH SEWING MACHINE  
“TYPICAL” MODEL 96 - 41



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

Model 96-41 is a single needle industrial machine for sewing with a straight lock-stitch. The shuttle is driven by gears and provided with a reversible feed.

When operating at the highest speed, the machine runs smoothly without appreciable vibration. All components are made of first grade materials, the moving parts being of heat treated steel. The machine is suitable for weaving mills or uniform factories, and for manufacture of shirts and underwears.

The machine can be supplied with either treadle drive stand or electric drive stand, in the latter case it is fitted with a knee press by which the presser foot can be raised when the operator's hands are engaged.

Length of stitch	4 mm.
Maximum sewing speed	2500 stitches per minute
Working space under arm	265 x 165 mm.
Thickness of material sewn	7 mm.
Power required	$\frac{1}{2}$ H.

#### Packing Information


Contents	Approximate Weight (kgs)		Approximate Measurement (cm)
	Nett	Gross	
Treadle Stand	55	83	164 x 103 x 69
Head	23	33	62 x 28 x 46

N.B.—For improvement of the machine we reserve the right to alter either the design or the specification.

CODE: RT-3007

## “飛人”牌45K-50型工業用縫紉機 (供印刷廠訂書用亦適用於皮革及蓬帆製品)

### LOCKSTITCH SEWING MACHINE “FLYING MAN” MODEL 45K-50



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
HONG KONG Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRCO."

Model 45K-50 embodies the latest improvement in design. Its sturdy construction ensures durability and long serviceable life. All moving parts, made of high grade steel, are hardened and precision ground.

The machine is especially suitable for sewing heavy canvas or leather goods, as used in the manufacture of wagon covers, sails, heavy sacks, upholsteries, leather belts and other leather handicrafts.

It is fitted with an exceptionally large cylinder shuttle of the oscillating type having a bobbin of great thread capacity which feature makes the machine specially adaptable for mass production.

This model is in all respects same as Model 45K-25 except that it is fitted with a vibrating presser. In this form of presser, the presser foot moves forward at each stitch in unison with the feed, rises and automatically returns to its former position, thus ensuring a uniform and perfect feed when stitching fabrics of uneven or adhesive surfaces. It is also particularly effective when stitching materials are liable to pucker such as book binding, etc. The machine sews with a long, firm and tightly drawn lock-stitch.

Being light running, the machine can be easily operated by foot in which case it is supplied with a treadle drive stand and a two-speed drive wheel for regulating the sewing speed. For mass production, the machine can be supplied with an electric drive stand and a knee press by which the presser foot can be raised while the operator's hands are engaged.

Length of stitch	12 mm.
Sewing speed	350 - 1000 stitches per minute
Thickness of material sewn	12 mm.
Working space under arm	275 x 185 mm.
Power required	$\frac{1}{2}$ HP.

#### Packing Information


Contents	Approximate Weight (kgs)		Approximate Measurement (cm)
	Nett	Gross	
1 set Head	44	60	

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

RT-3004

## "飛人"牌44-13型雙線連鎖縫紉機 (供服裝工廠用)

### CENTRAL BOBBIN SEWING MACHINE (WITH OSCILLATING SHUTTLE) "FLYING MAN" MODELE 44-13



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理商：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."



This is an indispensable machine for industrial use. The maximum speed is about 2000 stitches per minute. Aside from sewing light and medium weight fabrics, it also sews heavy weight materials such as canvas, leather, etc., and is especially suitable for mass production.

The machine shows the most judicious use of materials to resist strain and secure absolute stability. All running parts are carefully balanced so that there is no vibration to cause unusual wear of parts.

The machine can be supplied with either treadle drive stand or electric drive stand, in the latter case it is fitted with a knee press by which the presser foot can be raised when the operator's hands are engaged.

Length of stitch	4.5 mm.
Maximum sewing speed	2000 stitches per minute
Thickness of material sewn	5 mm.
Working space under arm	265 x 145 mm.
Power required	$\frac{1}{2}$ HP.
Stand	Treadle or Power

#### Packing Information

Contents	Approximate Weight (kgs)		Approximate Measurement (cm)
	Nett	Gross	
2 sets Head	39	49	55 x 45 x 43
2 sets Table & Stand	70	86	101 x 76 x 33


N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

CODE: RT - 3003

## “飛人”牌61300型工業用縫紉機

(供被服廠針織廠縫製棉毛織物服裝用)

### LOCKSTITCH SEWING MACHINE “FLYING MAN” MODEL 61300



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理商：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."

CODE: RT-3006

This machine can be used advantageously in blanket factories, underwear factories, knitting mills and clothing factories for sewing cotton or woollen underweares and outerweares.

Constructed for two-thread lockstitch sewing, the main shaft runs at a very high speed of about 4000 stitches per minute, power being transmitted by canvas laminated bakelite gears ensuring smooth and silent running.

The essential working parts are heat treated and precision ground thereby minimizing friction and wear, so that these parts are very durable.

By means of automatic lubrication, oil is continuously feed into the essential working parts so that the machine has a long serviceable life. An oil level gauge is provided for frequent inspection of the oil contents. The oil can be changed once every six months of continuous operation.

The machine is equipped with thread take-up and knee-press for raising presser-foot.

Length of stitch	4.5 mm.
Maximum sewing speed	4000 stitches per minute
Thickness of material sewn	5 mm.
Working space under arm	275 x 110 mm.
Overall dimension	510 x 20 x 290 mm.
Power required	$\frac{1}{2}$ HP.
Stand	Electric or treadle drive


## Packing Information

Contents	Approximate Weight (kgs)		Approximate Measurement (cm)
	Nett	Gross	
1 set Head	30	42	66 x 35 x 42

N.B.—For improvement of the machine, we reserve the right to alter either the design or the specification.

“飛人”牌45K-25型工業用縫紉機  
(供縫製皮革篷帆布及布鞋底用)

CYLINDER ARM SEWING MACHINE  
“FLYING MAN” MODEL 45 K-25



中國運輸機械進口公司經售  
Exported by CHINA NATIONAL TRANSPORT MACHINERY IMPORT CORPORATION  
香港代理處：華潤公司  
Hong Kong Agency: CHINA RESOURCES CO.  
BANK OF CHINA BUILDING  
HONG KONG  
CABLE ADDRESS: "CIRECO."